

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1270195

Luminaire Tested: P3AS17R359740DE010 E3DL1WH

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1270195  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-17)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS17R359740DE010 E3DL1WH  
Description: 3in Adjustable LED luminaire with, R35 optic, 4000K CCT AND, 97CRI , E3DL1WH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 809.0 lumens  
Efficiency: N/A  
Efficacy: 38.2 lumens/watt  
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.72  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 21.2  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1270195

CATALOG NUMBER: P3AS17R359740DE010 E3DL1WH

### Luminous Intensity Polar Plot



TEST NUMBER: P1270195

CATALOG NUMBER: P3AS17R359740DE010 E3DL1WH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 108 | 105 | 111 | 108 | 106 | 104 | 104 | 102 | 100 |  | 100 | 99  | 97  |  | 97  |
| 2   | 107 | 102 | 98  | 94  | 105 | 100 | 97  | 93  | 97  | 94  | 91  |  | 94  | 92  | 89  |  | 91  |
| 3   | 102 | 95  | 90  | 86  | 100 | 94  | 89  | 85  | 91  | 87  | 84  |  | 89  | 85  | 82  |  | 86  |
| 4   | 97  | 89  | 83  | 79  | 95  | 88  | 82  | 78  | 86  | 81  | 77  |  | 84  | 80  | 77  |  | 82  |
| 5   | 92  | 83  | 77  | 73  | 90  | 82  | 77  | 73  | 81  | 76  | 72  |  | 79  | 75  | 71  |  | 77  |
| 6   | 87  | 78  | 72  | 68  | 86  | 77  | 72  | 68  | 76  | 71  | 67  |  | 75  | 70  | 67  |  | 73  |
| 7   | 83  | 74  | 68  | 63  | 82  | 73  | 67  | 63  | 72  | 67  | 63  |  | 71  | 66  | 63  |  | 69  |
| 8   | 79  | 70  | 64  | 60  | 78  | 69  | 63  | 59  | 68  | 63  | 59  |  | 67  | 62  | 59  |  | 66  |
| 9   | 76  | 66  | 60  | 56  | 75  | 66  | 60  | 56  | 65  | 59  | 56  |  | 64  | 59  | 56  |  | 63  |
| 10  | 72  | 63  | 57  | 53  | 71  | 62  | 57  | 53  | 61  | 56  | 53  |  | 61  | 56  | 53  |  | 60  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 260045 |
| 5°  | 253620 |
| 10° | 231882 |
| 15° | 196823 |
| 20° | 155810 |
| 25° | 117829 |
| 30° | 85785  |
| 35° | 58009  |
| 40° | 35667  |
| 45° | 20467  |
| 50° | 12315  |
| 55° | 10016  |
| 60° | 8727   |
| 65° | 7731   |
| 70° | 6411   |
| 75° | 6354   |
| 80° | 6314   |
| 85° | 6290   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 20467 cd/sqm

TEST NUMBER: P1270195

CATALOG NUMBER: P3AS17R359740DE010 E3DL1WH

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 106.5  | 13.2      |
| 10°-20°   | 239.0  | 29.5      |
| 20°-30°   | 223.6  | 27.6      |
| 30°-40°   | 136.8  | 16.9      |
| 40°-50°   | 53.9   | 6.7       |
| 50°-60°   | 23.8   | 2.9       |
| 60°-70°   | 14.8   | 1.8       |
| 70°-80°   | 7.9    | 1.0       |
| 80°-90°   | 2.7    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 569.1  | 70.3      |
| 0°-40°    | 705.9  | 87.3      |
| 0°-60°    | 783.6  | 96.9      |
| 0°-90°    | 809.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 809.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1186 |      |
| 5°  | 1152 | 106  |
| 15° | 867  | 239  |
| 25° | 487  | 224  |
| 35° | 217  | 137  |
| 45° | 66   | 54   |
| 55° | 26   | 24   |
| 65° | 15   | 15   |
| 75° | 8    | 8    |
| 85° | 2    | 3    |
| 90° | 0    |      |

TEST NUMBER: P1270195

CATALOG NUMBER: P3AS17R359740DE010 E3DL1WH

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 1185.9 |
| 1°    | 1187.1 |
| 2°    | 1183.4 |
| 3°    | 1175.9 |
| 4°    | 1164.7 |
| 5°    | 1152.2 |
| 6°    | 1136.0 |
| 7°    | 1117.3 |
| 8°    | 1094.9 |
| 9°    | 1070.0 |
| 10°   | 1041.4 |
| 11°   | 1011.5 |
| 12°   | 979.1  |
| 13°   | 944.2  |
| 14°   | 905.6  |
| 15°   | 867.0  |
| 17.5° | 767.3  |
| 20°   | 667.7  |
| 22.5° | 571.8  |
| 25°   | 487.0  |
| 27.5° | 408.6  |
| 30°   | 338.8  |
| 32.5° | 274.0  |
| 35°   | 216.7  |
| 37.5° | 165.7  |
| 40°   | 124.6  |
| 42.5° | 89.7   |
| 45°   | 66.0   |
| 47.5° | 47.3   |
| 50°   | 36.1   |
| 52.5° | 29.9   |
| 55°   | 26.2   |
| 57.5° | 22.4   |
| 60°   | 19.9   |
| 62.5° | 17.4   |
| 65°   | 14.9   |
| 67.5° | 12.5   |
| 70°   | 10.0   |
| 72.5° | 8.7    |
| 75°   | 7.5    |
| 77.5° | 6.2    |
| 80°   | 5.0    |
| 82.5° | 3.7    |
| 85°   | 2.5    |
| 87.5° | 1.2    |



TEST NUMBER: P1270195

CATALOG NUMBER: P3AS17R359740DE010 E3DL1WH

CANDELA DISTRIBUTION (continued):



(END OF REPORT)