

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1270254

Luminaire Tested: P3AS17R459740DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1270254
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-26)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R459740DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R45 optic, 4000K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 530.0 lumens
Efficiency: N/A
Efficacy: 25.0 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.92
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1270254

CATALOG NUMBER: P3AS17R459740DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1270254

CATALOG NUMBER: P3AS17R459740DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	97	96		96
2	106	100	95	91	103	98	94	90	95	91	88		92	89	86		89
3	99	92	86	82	97	90	85	81	88	83	80		85	81	78		83
4	94	85	78	74	92	84	78	73	81	76	72		79	75	71		77
5	88	79	72	67	86	78	71	67	76	70	66		74	69	65		72
6	83	73	66	61	81	72	66	61	71	65	61		69	64	60		68
7	78	68	61	57	77	67	61	56	66	60	56		65	60	56		64
8	74	64	57	52	73	63	57	52	62	56	52		61	56	52		60
9	70	60	53	49	69	59	53	49	58	52	48		57	52	48		56
10	67	56	50	45	66	56	49	45	55	49	45		54	49	45		53

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	112381
5°	110389
10°	104451
15°	95256
20°	84241
25°	73141
30°	62794
35°	52334
40°	38987
45°	23878
50°	11053
55°	8640
60°	8289
65°	7627
70°	7052
75°	6693
80°	6188
85°	4529

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 23878 cd/sqm

TEST NUMBER: P1270254

CATALOG NUMBER: P3AS17R459740DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	46.8	8.8
10°-20°	116.8	22.0
20°-30°	138.8	26.2
30°-40°	120.6	22.8
40°-50°	60.5	11.4
50°-60°	21.0	4.0
60°-70°	14.7	2.8
70°-80°	8.2	1.5
80°-90°	2.5	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	302.5	57.1
0°-40°	423.1	79.8
0°-60°	504.6	95.2
0°-90°	530.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	530.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	512	
5°	502	47
15°	420	117
25°	302	139
35°	196	121
45°	77	60
55°	23	21
65°	15	15
75°	8	8
85°	2	2
90°	0	

TEST NUMBER: P1270254

CATALOG NUMBER: P3AS17R459740DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	512.5
2.5°	510.0
5°	501.5
7.5°	488.0
10°	469.1
12.5°	445.9
15°	419.6
17.5°	390.3
20°	361.0
22.5°	331.1
25°	302.3
27.5°	274.9
30°	248.0
32.5°	222.3
35°	195.5
37.5°	166.7
40°	136.2
42.5°	106.3
45°	77.0
47.5°	50.7
50°	32.4
52.5°	25.0
55°	22.6
57.5°	20.8
60°	18.9
62.5°	17.1
65°	14.7
67.5°	12.8
70°	11.0
72.5°	9.2
75°	7.9
77.5°	6.1
80°	4.9
82.5°	3.7
85°	1.8
87.5°	1.2
90°	0.0

(END OF REPORT)