

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1270632

Luminaire Tested: P3AS20R459740D010 E3DLD1GPH

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1270632  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-26)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS20R459740D010 E3DLD1GPH  
Description: 3in Adjustable LED luminaire with, R45 optic, 4000K CCT AND, 97CRI , E3DLD1GPH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 696.0 lumens  
Efficiency: N/A  
Efficacy: 24.2 lumens/watt  
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.92  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 28.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1270632  
CATALOG NUMBER: P3AS20R459740D010 E3DLD1GPH

### Luminous Intensity Polar Plot





TEST NUMBER: P1270632

CATALOG NUMBER: P3AS20R459740D010 E3DLD1GPH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91				91
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83				83
3	99	92	86	82	97	90	85	81	88	83	80	85	81	78	83	80	77	75				75
4	94	85	78	74	92	84	78	73	81	76	72	79	75	71	77	74	71	69				69
5	88	79	72	67	86	78	71	67	76	70	66	74	69	65	72	68	65	63				63
6	83	73	66	61	81	72	66	61	71	65	61	69	64	60	68	63	60	58				58
7	78	68	61	57	77	67	61	56	66	60	56	65	60	56	64	59	55	54				54
8	74	64	57	52	73	63	57	52	62	56	52	61	56	52	60	55	52	50				50
9	70	60	53	49	69	59	53	49	58	52	48	57	52	48	56	52	48	47				47
10	67	56	50	45	66	56	49	45	55	49	45	54	49	45	53	48	45	44				44

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	147576
5°	144948
10°	137161
15°	125086
20°	110610
25°	96054
30°	82468
35°	68717
40°	51210
45°	31352
50°	14498
55°	11354
60°	10920
65°	10014
70°	9232
75°	8811
80°	8082
85°	6038

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 31352 cd/sqm



TEST NUMBER: P1270632  
 CATALOG NUMBER: P3AS20R459740D010 E3DLD1GPH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	61.5	8.8
10°-20°	153.4	22.0
20°-30°	182.3	26.2
30°-40°	158.4	22.8
40°-50°	79.4	11.4
50°-60°	27.6	4.0
60°-70°	19.3	2.8
70°-80°	10.8	1.5
80°-90°	3.3	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	397.2	57.1
0°-40°	555.6	79.8
0°-60°	662.6	95.2
0°-90°	696.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	696.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	673	
5°	658	62
15°	551	153
25°	397	182
35°	257	158
45°	101	79
55°	30	28
65°	19	19
75°	10	11
85°	2	3
90°	0	

TEST NUMBER: P1270632

CATALOG NUMBER: P3AS20R459740D010 E3DLD1GPH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	673.0
2.5°	669.8
5°	658.5
7.5°	640.9
10°	616.0
12.5°	585.5
15°	551.0
17.5°	512.5
20°	474.0
22.5°	434.7
25°	397.0
27.5°	360.9
30°	325.7
32.5°	292.0
35°	256.7
37.5°	219.0
40°	178.9
42.5°	139.6
45°	101.1
47.5°	66.6
50°	42.5
52.5°	32.9
55°	29.7
57.5°	27.3
60°	24.9
62.5°	22.5
65°	19.3
67.5°	16.8
70°	14.4
72.5°	12.0
75°	10.4
77.5°	8.0
80°	6.4
82.5°	4.8
85°	2.4
87.5°	1.6
90°	0.0

(END OF REPORT)