

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1271051

Luminaire Tested: P3AS02R559827DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1271051
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R559827DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R55 optic, 2700K CCT AND, 98CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 215.0 lumens
Efficiency: N/A
Efficacy: 59.7 lumens/watt
Spacing Criteria (0/90/45): 0.93 / 0.93 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1271051

CATALOG NUMBER: P3AS02R559827DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1271051

CATALOG NUMBER: P3AS02R559827DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	112	109	107	105	105	104	102		102	100	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	104	98	94	90	102	97	93	90	95	91	88		92	89	87		90
4	100	93	88	84	98	92	87	84	90	86	83		88	84	82		86
5	95	88	82	79	94	87	82	78	85	81	78		84	80	77		82
6	91	83	78	74	90	82	77	74	81	76	73		80	76	73		78
7	87	79	73	70	86	78	73	69	77	72	69		76	72	69		75
8	83	75	69	66	82	74	69	65	73	69	65		72	68	65		71
9	80	71	66	62	79	71	66	62	70	65	62		69	65	62		68
10	77	68	62	59	76	67	62	59	67	62	59		66	62	59		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	62341
5°	60136
10°	62301
15°	61408
20°	56845
25°	45970
30°	27549
35°	9342
40°	2576
45°	1147
50°	341
55°	76
60°	44
65°	52
70°	64
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1147 cd/sqm

TEST NUMBER: P1271051

CATALOG NUMBER: P3AS02R559827DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	26.4	12.3
10°-20°	75.3	35.0
20°-30°	83.7	38.9
30°-40°	26.1	12.1
40°-50°	3.1	1.5
50°-60°	0.3	0.1
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	185.5	86.3
0°-40°	211.5	98.4
0°-60°	214.9	99.9
0°-90°	215.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	215.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	284	
5°	273	26
15°	270	75
25°	190	84
35°	35	26
45°	4	3
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1271051

CATALOG NUMBER: P3AS02R559827DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	284.3
1°	283.3
2°	280.5
3°	277.1
4°	274.0
5°	273.2
6°	274.0
7°	275.8
8°	277.7
9°	279.3
10°	279.8
11°	279.4
12°	278.1
13°	276.1
14°	273.7
15°	270.5
16°	266.8
17°	262.2
18°	257.0
19°	250.7
20°	243.6
21°	235.5
22°	225.9
23°	215.4
24°	203.3
25°	190.0
26°	175.4
27°	159.8
28°	143.3
29°	126.2
30°	108.8
31°	91.3
32°	74.2
32.5°	66.7
33°	58.8
34°	45.5
35°	34.9
36°	26.5
37°	19.7
37.5°	16.8
38°	14.6
39°	11.1
40°	9.0
42.5°	5.7
45°	3.7

TEST NUMBER: P1271051

CATALOG NUMBER: P3AS02R559827DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	2.2
50°	1.0
52.5°	0.3
55°	0.2
57.5°	0.1
60°	0.1
62.5°	0.1
65°	0.1
67.5°	0.1
70°	0.1
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)