

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1271080

Luminaire Tested: P3AS02R609827DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1271080
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R609827DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R60 optic, 2700K CCT AND, 98CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 199.1 lumens
Efficiency: N/A
Efficacy: 55.3 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1271080

CATALOG NUMBER: P3AS02R609827DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1271080

CATALOG NUMBER: P3AS02R609827DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	109	106	111	109	107	105	105	103	102	101	100	99	98	97	96	94		
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88		
3	103	97	92	88	101	96	91	88	93	89	86	91	87	85	88	86	84	82		
4	98	91	85	81	96	90	85	81	88	83	80	86	82	79	84	81	78	77		
5	93	85	80	75	92	84	79	75	83	78	74	81	77	74	79	76	73	72		
6	89	80	74	70	87	79	74	70	78	73	70	77	72	69	75	71	69	67		
7	85	76	70	66	83	75	69	65	74	69	65	72	68	65	71	67	64	63		
8	81	71	65	61	79	71	65	61	70	65	61	69	64	61	68	64	61	59		
9	77	67	62	58	76	67	61	58	66	61	57	65	61	57	64	60	57	56		
10	73	64	58	54	72	63	58	54	63	58	54	62	57	54	61	57	54	53		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	52145
5°	49218
10°	47939
15°	46856
20°	43567
25°	38930
30°	29751
35°	17159
40°	6670
45°	2791
50°	614
55°	76
60°	88
65°	52
70°	64
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2791 cd/sqm

TEST NUMBER: P1271080

CATALOG NUMBER: P3AS02R609827DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	21.1	10.6
10°-20°	57.5	28.9
20°-30°	72.0	36.2
30°-40°	40.2	20.2
40°-50°	7.7	3.9
50°-60°	0.4	0.2
60°-70°	0.1	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	150.6	75.7
0°-40°	190.8	95.9
0°-60°	198.9	99.9
0°-90°	199.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	199.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	238	
5°	224	21
15°	206	57
25°	161	72
35°	64	40
45°	9	8
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1271080

CATALOG NUMBER: P3AS02R609827DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	237.8
1°	236.8
2°	233.7
3°	230.0
4°	226.6
5°	223.6
6°	221.3
7°	219.4
8°	217.9
9°	216.5
10°	215.3
11°	214.1
12°	212.7
13°	211.0
14°	209.0
15°	206.4
16°	203.2
17°	199.6
18°	195.5
19°	190.9
20°	186.7
21°	182.1
22°	177.4
23°	172.4
24°	167.0
25°	160.9
26°	153.9
27°	146.0
28°	137.1
29°	127.6
30°	117.5
31°	107.2
32°	96.6
32.5°	90.8
33°	85.6
34°	74.8
35°	64.1
36°	54.5
37°	44.4
37.5°	39.7
38°	35.2
39°	28.3
40°	23.3
42.5°	14.2
45°	9.0



TEST NUMBER: P1271080

CATALOG NUMBER: P3AS02R609827DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	5.0
50°	1.8
52.5°	0.4
55°	0.2
57.5°	0.2
60°	0.2
62.5°	0.1
65°	0.1
67.5°	0.1
70°	0.1
72.5°	0.1
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)