

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1271203

Luminaire Tested: P3AS05R209827DE010 E3DL1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1271203
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-7)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R209827DE010 E3DL1MW
Description: 3in Adjustable LED luminaire with, R20 optic, 2700K CCT AND, 98CRI , E3DL1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 357.0 lumens
Efficiency: N/A
Efficacy: 49.6 lumens/watt
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.46
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1271203

CATALOG NUMBER: P3AS05R209827DE010 E3DL1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1271203

CATALOG NUMBER: P3AS05R209827DE010 E3DL1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	110	106	102	100	108	104	101	98	101	98	96		98	96	94		95
3	106	100	96	93	104	99	95	92	97	93	91		94	92	89		92
4	102	96	91	88	100	95	90	87	92	89	86		91	88	85		89
5	98	91	87	83	97	90	86	83	89	85	82		87	84	81		86
6	95	87	83	79	93	87	82	79	85	81	78		84	81	78		83
7	91	84	79	76	90	83	79	76	82	78	75		81	78	75		80
8	88	81	76	73	87	80	76	73	79	75	72		78	75	72		78
9	86	78	73	70	85	77	73	70	77	73	70		76	72	70		75
10	83	75	71	68	82	75	70	67	74	70	67		73	70	67		73

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	274671
5°	249680
10°	184521
15°	114144
20°	65199
25°	37212
30°	20864
35°	11350
40°	6212
45°	3411
50°	2013
55°	1453
60°	1360
65°	1245
70°	1090
75°	1186
80°	884
85°	755

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 3411 cd/sqm

TEST NUMBER: P1271203

CATALOG NUMBER: P3AS05R209827DE010 E3DL1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	98.2	27.5
10°-20°	140.2	39.3
20°-30°	73.2	20.5
30°-40°	28.3	7.9
40°-50°	9.2	2.6
50°-60°	3.6	1.0
60°-70°	2.4	0.7
70°-80°	1.4	0.4
80°-90°	0.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	311.6	87.3
0°-40°	339.9	95.2
0°-60°	352.7	98.8
0°-90°	357.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	357.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1253	
5°	1134	98
15°	503	140
25°	154	73
35°	42	28
45°	11	9
55°	4	4
65°	2	2
75°	1	1
85°	0	0
90°	0	

TEST NUMBER: P1271203

CATALOG NUMBER: P3AS05R209827DE010 E3DL1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	1252.6
1°	1250.2
2°	1235.4
3°	1212.6
4°	1177.4
5°	1134.3
6°	1083.3
7°	1026.7
8°	961.2
9°	897.4
10°	828.7
12.5°	658.7
15°	502.8
17.5°	376.3
20°	279.4
22.5°	206.9
25°	153.8
27.5°	113.5
30°	82.4
32.5°	59.7
35°	42.4
37.5°	30.7
40°	21.7
42.5°	15.5
45°	11.0
47.5°	7.9
50°	5.9
52.5°	4.5
55°	3.8
57.5°	3.4
60°	3.1
62.5°	2.8
65°	2.4
67.5°	2.1
70°	1.7
72.5°	1.7
75°	1.4
77.5°	1.0
80°	0.7
82.5°	0.7
85°	0.3
87.5°	0.3
90°	0.0

(END OF REPORT)