

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1271263

Luminaire Tested: P3AS05R309827DE010 E3DL1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1271263
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R309827DE010 E3DL1WMH
Description: 3in Adjustable LED luminaire with, R30 optic, 2700K CCT AND, 98CRI , E3DL1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 365.0 lumens
Efficiency: N/A
Efficacy: 50.7 lumens/watt
Spacing Criteria (0/90/45): 0.54 / 0.54 / 0.54
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1271263

CATALOG NUMBER: P3AS05R309827DE010 E3DL1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1271263

CATALOG NUMBER: P3AS05R309827DE010 E3DL1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	110	105	102	99	107	104	101	98	101	98	96		98	96	94		95
3	105	100	96	92	103	98	95	91	96	93	90		94	91	89		91
4	101	95	90	87	99	94	89	86	92	88	85		90	87	84		88
5	97	90	85	82	96	89	85	81	88	84	81		86	83	80		85
6	94	86	81	78	92	85	81	77	84	80	77		83	79	76		81
7	90	82	77	74	89	82	77	74	81	76	73		80	76	73		79
8	87	79	74	71	86	79	74	71	78	73	70		77	73	70		76
9	84	76	71	68	83	75	71	68	75	70	67		74	70	67		73
10	81	73	68	65	80	73	68	65	72	68	65		71	67	65		71

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	212987
5°	202729
10°	170516
15°	122975
20°	76283
25°	43382
30°	24105
35°	13117
40°	6899
45°	3752
50°	2013
55°	1300
60°	1228
65°	1245
70°	1090
75°	847
80°	884
85°	755

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 3752 cd/sqm

TEST NUMBER: P1271263

CATALOG NUMBER: P3AS05R309827DE010 E3DL1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	82.9	22.7
10°-20°	147.4	40.4
20°-30°	85.2	23.3
30°-40°	32.3	8.9
40°-50°	9.9	2.7
50°-60°	3.3	0.9
60°-70°	2.3	0.6
70°-80°	1.2	0.3
80°-90°	0.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	315.5	86.5
0°-40°	347.9	95.3
0°-60°	361.1	98.9
0°-90°	365.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	365.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	971	
5°	921	83
15°	542	147
25°	179	85
35°	49	32
45°	12	10
55°	3	3
65°	2	2
75°	1	1
85°	0	0
90°	0	

TEST NUMBER: P1271263

CATALOG NUMBER: P3AS05R309827DE010 E3DL1WMH

CANDELA DISTRIBUTION (FULL):


0°	
0°	971.3
1°	970.6
2°	964.8
3°	953.7
4°	939.9
5°	921.0
6°	896.8
7°	869.9
8°	839.9
9°	804.1
10°	765.8
11°	724.4
12°	680.6
13°	634.8
14°	588.2
15°	541.7
17.5°	427.2
20°	326.9
22.5°	242.4
25°	179.3
27.5°	130.3
30°	95.2
32.5°	68.6
35°	49.0
37.5°	34.1
40°	24.1
42.5°	16.9
45°	12.1
47.5°	8.3
50°	5.9
52.5°	4.1
55°	3.4
57.5°	3.1
60°	2.8
62.5°	2.4
65°	2.4
67.5°	2.1
70°	1.7
72.5°	1.4
75°	1.0
77.5°	1.0
80°	0.7
82.5°	0.7
85°	0.3
87.5°	0.0



TEST NUMBER: P1271263

CATALOG NUMBER: P3AS05R309827DE010 E3DL1WMH

CANDELA DISTRIBUTION (continued):



(END OF REPORT)