

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1271328

Luminaire Tested: P3AS05R409827DE010 E3DLD1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1271328
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-22)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R409827DE010 E3DLD1WH
Description: 3in Adjustable LED luminaire with, R40 optic, 2700K CCT AND, 98CRI , E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 308.0 lumens
Efficiency: N/A
Efficacy: 42.8 lumens/watt
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1271328

CATALOG NUMBER: P3AS05R409827DE010 E3DLD1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1271328

CATALOG NUMBER: P3AS05R409827DE010 E3DLD1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	98	96		96
2	106	100	96	92	104	98	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	75	72		78
5	89	79	73	68	87	78	72	67	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	61		70	65	61		68
7	79	69	62	57	78	68	62	57	67	61	57		65	60	57		64
8	75	64	58	53	74	64	58	53	63	57	53		62	56	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	51	46	66	56	50	46	56	50	46		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	69139
5°	67884
10°	63993
15°	58116
20°	51058
25°	43599
30°	36132
35°	27867
40°	19837
45°	13366
50°	7300
55°	5123
60°	4824
65°	4462
70°	3975
75°	3813
80°	3031
85°	2516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 13366 cd/sqm

TEST NUMBER: P1271328

CATALOG NUMBER: P3AS05R409827DE010 E3DLD1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	28.8	9.3
10°-20°	71.3	23.2
20°-30°	82.5	26.8
30°-40°	65.0	21.1
40°-50°	33.4	10.8
50°-60°	12.8	4.1
60°-70°	8.4	2.7
70°-80°	4.6	1.5
80°-90°	1.4	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	182.5	59.3
0°-40°	247.5	80.4
0°-60°	293.6	95.3
0°-90°	308.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	308.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	315	
5°	308	29
15°	256	71
25°	180	82
35°	104	65
45°	43	33
55°	13	13
65°	9	8
75°	4	5
85°	1	1
90°	0	

TEST NUMBER: P1271328

CATALOG NUMBER: P3AS05R409827DE010 E3DLD1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	315.3
2.5°	313.6
5°	308.4
7.5°	299.5
10°	287.4
12.5°	273.3
15°	256.0
17.5°	238.1
20°	218.8
22.5°	199.2
25°	180.2
27.5°	161.3
30°	142.7
32.5°	123.7
35°	104.1
37.5°	85.8
40°	69.3
42.5°	55.1
45°	43.1
47.5°	31.4
50°	21.4
52.5°	15.5
55°	13.4
57.5°	12.1
60°	11.0
62.5°	9.6
65°	8.6
67.5°	7.2
70°	6.2
72.5°	5.2
75°	4.5
77.5°	3.4
80°	2.4
82.5°	2.1
85°	1.0
87.5°	0.7
90°	0.0

(END OF REPORT)