

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1271367

Luminaire Tested: P3AS05R509827DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1271367
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R509827DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R50 optic, 2700K CCT AND, 98CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 479.0 lumens
Efficiency: N/A
Efficacy: 66.5 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1271367

CATALOG NUMBER: P3AS05R509827DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1271367

CATALOG NUMBER: P3AS05R509827DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	109	107	112	110	108	106	105	104	102		102	101	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	105	99	95	91	103	98	94	90	95	92	89		93	90	88		91
4	100	94	89	85	99	92	88	85	90	87	84		88	85	83		87
5	96	89	84	80	94	88	83	79	86	82	79		84	81	78		83
6	92	84	79	75	91	83	78	75	82	78	74		81	77	74		79
7	88	80	75	71	87	79	74	71	78	74	70		77	73	70		76
8	84	76	71	67	83	76	71	67	75	70	67		74	69	66		73
9	81	73	67	64	80	72	67	64	71	67	63		70	66	63		70
10	78	69	64	61	77	69	64	61	68	64	60		67	63	60		67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	167399
5°	162932
10°	155486
15°	140773
20°	121787
25°	99901
30°	57376
35°	17828
40°	4780
45°	1675
50°	409
55°	115
60°	88
65°	104
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1675 cd/sqm

TEST NUMBER: P1271367

CATALOG NUMBER: P3AS05R509827DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	69.3	14.5
10°-20°	171.8	35.9
20°-30°	180.6	37.7
30°-40°	51.7	10.8
40°-50°	5.0	1.1
50°-60°	0.4	0.1
60°-70°	0.2	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	421.7	88.0
0°-40°	473.4	98.8
0°-60°	478.8	100.0
0°-90°	479.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	479.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	763	
5°	740	69
15°	620	172
25°	413	181
35°	67	52
45°	5	5
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1271367

CATALOG NUMBER: P3AS05R509827DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	763.4
1°	762.2
2°	758.8
3°	753.9
4°	747.3
5°	740.2
6°	732.6
7°	724.5
8°	716.9
9°	708.1
10°	698.3
11°	687.0
12°	674.0
13°	657.7
14°	640.2
15°	620.1
16°	598.8
17°	578.1
18°	557.0
19°	538.4
20°	521.9
21°	506.0
22°	487.9
23°	467.1
24°	442.8
25°	412.9
26°	380.4
27°	344.2
28°	308.3
29°	269.4
30°	226.6
31°	186.6
32°	149.7
32.5°	133.7
33°	117.5
34°	90.1
35°	66.6
36°	48.8
37°	36.3
37.5°	31.4
38°	27.2
39°	21.1
40°	16.7
42.5°	9.5
45°	5.4

TEST NUMBER: P1271367

CATALOG NUMBER: P3AS05R509827DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	3.0
50°	1.2
52.5°	0.5
55°	0.3
57.5°	0.3
60°	0.2
62.5°	0.2
65°	0.2
67.5°	0.2
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)