

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1271604

Luminaire Tested: P3AS09R309827DE010 E3DL1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1271604
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R309827DE010 E3DL1H
Description: 3in Adjustable LED luminaire with, R30 optic, 2700K CCT AND, 98CRI , E3DL1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 539.0 lumens
Efficiency: N/A
Efficacy: 49.0 lumens/watt
Spacing Criteria (0/90/45): 0.54 / 0.54 / 0.54
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1271604

CATALOG NUMBER: P3AS09R309827DE010 E3DL1H

Luminous Intensity Polar Plot



TEST NUMBER: P1271604

CATALOG NUMBER: P3AS09R309827DE010 E3DL1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	110	105	102	99	107	104	101	98	101	98	96		98	96	94		95
3	105	100	96	92	103	98	95	91	96	93	90		94	91	89		91
4	101	95	90	87	99	94	89	86	92	88	85		90	87	84		88
5	97	90	85	82	96	89	85	81	88	84	81		86	83	80		85
6	94	86	81	78	92	85	81	77	84	80	77		83	79	76		81
7	90	82	77	74	89	82	77	74	81	76	73		80	76	73		79
8	87	79	74	71	86	79	74	71	78	73	70		77	73	70		76
9	84	76	71	68	83	75	71	68	75	70	67		74	70	67		73
10	81	73	68	65	80	73	68	65	72	68	65		71	67	65		71

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	314514
5°	299361
10°	251810
15°	181590
20°	112640
25°	64068
30°	35575
35°	19354
40°	10191
45°	5520
50°	2968
55°	1950
60°	1798
65°	1868
70°	1603
75°	1271
80°	1263
85°	1258

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5520 cd/sqm

TEST NUMBER: P1271604

CATALOG NUMBER: P3AS09R309827DE010 E3DL1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	122.5	22.7
10°-20°	217.7	40.4
20°-30°	125.8	23.3
30°-40°	47.7	8.9
40°-50°	14.6	2.7
50°-60°	4.9	0.9
60°-70°	3.4	0.6
70°-80°	1.8	0.3
80°-90°	0.5	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	466.0	86.5
0°-40°	513.7	95.3
0°-60°	533.3	98.9
0°-90°	539.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	539.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1434	
5°	1360	122
15°	800	218
25°	265	126
35°	72	48
45°	18	15
55°	5	5
65°	4	3
75°	2	2
85°	0	1
90°	0	



TEST NUMBER: P1271604

CATALOG NUMBER: P3AS09R309827DE010 E3DL1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1434.3
1°	1433.3
2°	1424.7
3°	1408.4
4°	1388.0
5°	1360.0
6°	1324.4
7°	1284.6
8°	1240.3
9°	1187.4
10°	1130.9
11°	1069.8
12°	1005.1
13°	937.4
14°	868.6
15°	799.9
17.5°	630.9
20°	482.7
22.5°	357.9
25°	264.8
27.5°	192.5
30°	140.5
32.5°	101.3
35°	72.3
37.5°	50.4
40°	35.6
42.5°	24.9
45°	17.8
47.5°	12.2
50°	8.7
52.5°	6.1
55°	5.1
57.5°	4.6
60°	4.1
62.5°	3.6
65°	3.6
67.5°	3.1
70°	2.5
72.5°	2.0
75°	1.5
77.5°	1.5
80°	1.0
82.5°	1.0
85°	0.5
87.5°	0.0



TEST NUMBER: P1271604
CATALOG NUMBER: P3AS09R309827DE010 E3DL1H

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)