

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1271658

Luminaire Tested: P3AS09R409827DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1271658
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-12)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R409827DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R40 optic, 2700K CCT AND, 98CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 712.9 lumens
Efficiency: N/A
Efficacy: 64.8 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1271658

CATALOG NUMBER: P3AS09R409827DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1271658

CATALOG NUMBER: P3AS09R409827DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		96
3	107	102	98	95	105	100	97	94	98	95	93		96	93	91		93
4	103	97	93	90	101	96	92	89	94	91	88		92	89	87		90
5	99	93	89	85	98	92	88	85	91	87	84		89	86	84		88
6	96	89	85	81	95	89	84	81	87	83	81		86	83	80		85
7	93	86	81	78	92	85	81	78	84	80	78		83	80	77		82
8	90	83	78	75	89	82	78	75	81	77	75		80	77	74		79
9	87	80	75	72	86	79	75	72	78	75	72		78	74	72		77
10	84	77	72	70	83	77	72	69	76	72	69		75	72	69		75

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	363436
5°	360818
10°	351363
15°	313872
20°	208105
25°	77956
30°	20864
35°	8165
40°	2920
45°	1395
50°	409
55°	191
60°	88
65°	104
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1395 cd/sqm

TEST NUMBER: P1271658

CATALOG NUMBER: P3AS09R409827DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	154.7	21.7
10°-20°	366.3	51.4
20°-30°	166.1	23.3
30°-40°	21.5	3.0
40°-50°	3.7	0.5
50°-60°	0.4	0.1
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	687.1	96.4
0°-40°	708.7	99.4
0°-60°	712.8	100.0
0°-90°	712.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	712.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1657	
5°	1639	155
15°	1383	366
25°	322	166
35°	30	22
45°	4	4
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1271658

CATALOG NUMBER: P3AS09R409827DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1657.4
1°	1656.4
2°	1653.9
3°	1650.1
4°	1645.4
5°	1639.2
6°	1631.9
7°	1622.9
8°	1612.0
9°	1597.0
10°	1578.0
11°	1555.8
12°	1526.1
13°	1489.4
14°	1441.5
15°	1382.6
16°	1307.4
17°	1221.8
18°	1119.0
19°	1010.4
20°	891.8
21°	773.3
22°	656.5
23°	540.1
24°	425.8
25°	322.2
26°	238.6
27°	174.7
28°	131.3
29°	102.1
30°	82.4
31°	68.1
32°	56.9
32.5°	51.9
33°	46.9
34°	38.2
35°	30.5
36°	24.0
37°	19.0
37.5°	17.0
38°	15.0
39°	12.5
40°	10.2
42.5°	6.7
45°	4.5



TEST NUMBER: P1271658

CATALOG NUMBER: P3AS09R409827DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	2.7
50°	1.2
52.5°	0.5
55°	0.5
57.5°	0.2
60°	0.2
62.5°	0.2
65°	0.2
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)