

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1272243

Luminaire Tested: P3AS17R209827DE010 E3DLD1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1272243
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-6)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R209827DE010 E3DLD1MW
Description: 3in Adjustable LED luminaire with, R20 optic, 2700K CCT AND, 98CRI , E3DLD1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 862.0 lumens
Efficiency: N/A
Efficacy: 42.3 lumens/watt
Spacing Criteria (0/90/45): 0.76 / 0.76 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 20.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1272243

CATALOG NUMBER: P3AS17R209827DE010 E3DLD1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1272243

CATALOG NUMBER: P3AS17R209827DE010 E3DLD1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		90
3	100	93	87	82	98	91	86	82	88	84	80		86	82	79		84
4	94	86	79	75	92	85	79	74	82	77	73		80	76	72		78
5	89	80	73	68	87	79	73	68	77	71	67		75	70	67		73
6	84	74	68	63	82	73	67	63	72	66	62		70	65	62		69
7	80	69	63	58	78	69	62	58	67	62	58		66	61	57		65
8	75	65	59	54	74	64	58	54	63	58	54		62	57	53		61
9	72	61	55	50	70	61	55	50	60	54	50		59	54	50		58
10	68	58	51	47	67	57	51	47	56	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	213207
5°	207528
10°	190912
15°	168037
20°	144119
25°	121072
30°	97863
35°	74445
40°	52985
45°	34980
50°	21662
55°	14222
60°	12981
65°	11934
70°	11220
75°	10167
80°	9723
85°	8303

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 34980 cd/sqm

TEST NUMBER: P1272243

CATALOG NUMBER: P3AS17R209827DE010 E3DLD1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	87.2	10.1
10°-20°	206.1	23.9
20°-30°	228.7	26.5
30°-40°	174.5	20.2
40°-50°	89.3	10.4
50°-60°	36.7	4.3
60°-70°	22.9	2.7
70°-80°	12.8	1.5
80°-90°	3.7	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	522.0	60.6
0°-40°	696.5	80.8
0°-60°	822.5	95.4
0°-90°	862.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	862.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	972	
5°	943	87
15°	740	206
25°	500	229
35°	278	174
45°	113	89
55°	37	37
65°	23	23
75°	12	13
85°	3	4
90°	0	

TEST NUMBER: P1272243

CATALOG NUMBER: P3AS17R209827DE010 E3DLD1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	972.3
1°	973.4
2°	969.1
3°	963.6
4°	954.8
5°	942.8
6°	928.5
7°	913.2
8°	896.8
9°	877.1
10°	857.4
12.5°	800.4
15°	740.2
17.5°	678.9
20°	617.6
22.5°	556.3
25°	500.4
27.5°	444.6
30°	386.5
32.5°	331.8
35°	278.1
37.5°	231.0
40°	185.1
42.5°	145.6
45°	112.8
47.5°	85.4
50°	63.5
52.5°	47.1
55°	37.2
57.5°	33.9
60°	29.6
62.5°	26.3
65°	23.0
67.5°	19.7
70°	17.5
72.5°	14.2
75°	12.0
77.5°	9.9
80°	7.7
82.5°	5.5
85°	3.3
87.5°	1.1
90°	0.0

(END OF REPORT)