

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1272613

Luminaire Tested: P3AS20R259827D010 E3DLD1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1272613
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R259827D010 E3DLD1H
Description: 3in Adjustable LED luminaire with, R25 optic, 2700K CCT AND, 98CRI , E3DLD1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1142.0 lumens
Efficiency: N/A
Efficacy: 41.7 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1272613

CATALOG NUMBER: P3AS20R259827D010 E3DLD1H

Luminous Intensity Polar Plot



TEST NUMBER: P1272613

CATALOG NUMBER: P3AS20R259827D010 E3DLD1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	271404
5°	264934
10°	245509
15°	218662
20°	187896
25°	159711
30°	131489
35°	102446
40°	73710
45°	46765
50°	27666
55°	19039
60°	17455
65°	16240
70°	14618
75°	13217
80°	12628
85°	10819

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 46765 cd/sqm

TEST NUMBER: P1272613

CATALOG NUMBER: P3AS20R259827D010 E3DLD1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	111.6	9.8
10°-20°	267.4	23.4
20°-30°	302.1	26.5
30°-40°	239.0	20.9
40°-50°	120.7	10.6
50°-60°	48.3	4.2
60°-70°	31.0	2.7
70°-80°	17.1	1.5
80°-90°	4.8	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	681.1	59.6
0°-40°	920.1	80.6
0°-60°	1089.1	95.4
0°-90°	1142.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1142.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1238	
5°	1204	112
15°	963	267
25°	660	302
35°	383	239
45°	151	121
55°	50	48
65°	31	31
75°	16	17
85°	4	5
90°	0	

TEST NUMBER: P1272613

CATALOG NUMBER: P3AS20R259827D010 E3DLD1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1237.7
1°	1237.7
2°	1233.5
3°	1226.4
4°	1216.4
5°	1203.6
6°	1187.9
7°	1169.5
8°	1149.5
9°	1126.8
10°	1102.6
11°	1075.6
12°	1049.9
13°	1020.1
14°	991.6
15°	963.2
17.5°	883.5
20°	805.2
22.5°	731.3
25°	660.1
27.5°	590.4
30°	519.3
32.5°	452.4
35°	382.7
37.5°	318.7
40°	257.5
42.5°	200.6
45°	150.8
47.5°	112.4
50°	81.1
52.5°	61.2
55°	49.8
57.5°	45.5
60°	39.8
62.5°	35.6
65°	31.3
67.5°	27.0
70°	22.8
72.5°	19.9
75°	15.6
77.5°	12.8
80°	10.0
82.5°	7.1
85°	4.3
87.5°	1.4



TEST NUMBER: P1272613
CATALOG NUMBER: P3AS20R259827D010 E3DLD1H

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)