

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1272719

Luminaire Tested: P3AS20R459827D010 E3CD1MB

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1272719  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-28)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS20R459827D010 E3CD1MB  
Description: 3in Adjustable LED luminaire with, R45 optic, 2700K CCT AND, 98CRI , E3CD1MB TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1907.0 lumens  
Efficiency: N/A  
Efficacy: 69.6 lumens/watt  
Spacing Criteria (0/90/45): 0.72 / 0.72 / 0.66  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 27.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1272719

CATALOG NUMBER: P3AS20R459827D010 E3CD1MB

### Luminous Intensity Polar Plot



TEST NUMBER: P1272719

CATALOG NUMBER: P3AS20R459827D010 E3CD1MB

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 114 | 112 | 110 | 108 | 112 | 110 | 108 | 106 | 106 | 104 | 103 |  | 102 | 101 | 100 |  | 99  |
| 2   | 110 | 106 | 102 | 100 | 108 | 104 | 101 | 98  | 101 | 98  | 96  |  | 98  | 96  | 94  |  | 95  |
| 3   | 106 | 100 | 96  | 93  | 104 | 99  | 95  | 92  | 96  | 93  | 91  |  | 94  | 91  | 89  |  | 92  |
| 4   | 102 | 95  | 91  | 87  | 100 | 94  | 90  | 87  | 92  | 89  | 86  |  | 90  | 87  | 85  |  | 88  |
| 5   | 98  | 91  | 86  | 82  | 96  | 90  | 85  | 82  | 88  | 84  | 81  |  | 87  | 83  | 81  |  | 85  |
| 6   | 94  | 87  | 82  | 78  | 93  | 86  | 81  | 78  | 85  | 80  | 77  |  | 83  | 80  | 77  |  | 82  |
| 7   | 90  | 83  | 78  | 74  | 89  | 82  | 78  | 74  | 81  | 77  | 74  |  | 80  | 76  | 74  |  | 79  |
| 8   | 87  | 79  | 74  | 71  | 86  | 79  | 74  | 71  | 78  | 74  | 71  |  | 77  | 73  | 70  |  | 76  |
| 9   | 84  | 76  | 71  | 68  | 83  | 76  | 71  | 68  | 75  | 71  | 68  |  | 74  | 70  | 67  |  | 73  |
| 10  | 81  | 73  | 68  | 65  | 80  | 73  | 68  | 65  | 72  | 68  | 65  |  | 71  | 67  | 65  |  | 71  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 826798 |
| 5°  | 831189 |
| 10° | 805663 |
| 15° | 675146 |
| 20° | 516085 |
| 25° | 314171 |
| 30° | 130729 |
| 35° | 41894  |
| 40° | 13024  |
| 45° | 2636   |
| 50° | 1944   |
| 55° | 2179   |
| 60° | 1886   |
| 65° | 2231   |
| 70° | 1795   |
| 75° | 2372   |
| 80° | 1768   |
| 85° | 0      |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2636 cd/sqm

TEST NUMBER: P1272719

CATALOG NUMBER: P3AS20R459827D010 E3CD1MB

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 356.1  | 18.7      |
| 10°-20°   | 817.4  | 42.9      |
| 20°-30°   | 588.5  | 30.9      |
| 30°-40°   | 122.4  | 6.4       |
| 40°-50°   | 11.2   | 0.6       |
| 50°-60°   | 4.6    | 0.2       |
| 60°-70°   | 3.7    | 0.2       |
| 70°-80°   | 2.4    | 0.1       |
| 80°-90°   | 0.6    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 1762.0 | 92.4      |
| 0°-40°    | 1884.5 | 98.8      |
| 0°-60°    | 1900.3 | 99.7      |
| 0°-90°    | 1907.0 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 1907.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 3770 |      |
| 5°  | 3776 | 356  |
| 15° | 2974 | 817  |
| 25° | 1298 | 589  |
| 35° | 156  | 122  |
| 45° | 8    | 11   |
| 55° | 6    | 5    |
| 65° | 4    | 4    |
| 75° | 3    | 2    |
| 85° | 0    | 1    |
| 90° | 0    |      |

TEST NUMBER: P1272719

CATALOG NUMBER: P3AS20R459827D010 E3CD1MB

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 3770.5 |
| 2.5°  | 3771.9 |
| 5°    | 3776.1 |
| 7.5°  | 3749.1 |
| 10°   | 3618.3 |
| 12.5° | 3345.2 |
| 15°   | 2974.0 |
| 17.5° | 2594.2 |
| 20°   | 2211.6 |
| 22.5° | 1772.2 |
| 25°   | 1298.5 |
| 27.5° | 856.2  |
| 30°   | 516.3  |
| 32.5° | 288.7  |
| 35°   | 156.5  |
| 37.5° | 88.2   |
| 40°   | 45.5   |
| 42.5° | 19.9   |
| 45°   | 8.5    |
| 47.5° | 5.7    |
| 50°   | 5.7    |
| 52.5° | 5.7    |
| 55°   | 5.7    |
| 57.5° | 4.3    |
| 60°   | 4.3    |
| 62.5° | 4.3    |
| 65°   | 4.3    |
| 67.5° | 2.8    |
| 70°   | 2.8    |
| 72.5° | 2.8    |
| 75°   | 2.8    |
| 77.5° | 1.4    |
| 80°   | 1.4    |
| 82.5° | 1.4    |
| 85°   | 0.0    |
| 87.5° | 0.0    |
| 90°   | 0.0    |

(END OF REPORT)