

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1272725

Luminaire Tested: P3AS20R459827D010 E3DL1LI

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1272725  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-27)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS20R459827D010 E3DL1LI  
Description: 3in Adjustable LED luminaire with, R45 optic, 2700K CCT AND, 98CRI , E3DL1LI TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1590.0 lumens  
Efficiency: N/A  
Efficacy: 58.0 lumens/watt  
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.69  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 27.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1272725

CATALOG NUMBER: P3AS20R459827D010 E3DL1LI

### Luminous Intensity Polar Plot



TEST NUMBER: P1272725

CATALOG NUMBER: P3AS20R459827D010 E3DL1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 114 | 111 | 109 | 107 | 111 | 109 | 107 | 105 | 105 | 103 | 102 |  | 101 | 100 | 99  |  | 98  |
| 2   | 109 | 104 | 100 | 97  | 106 | 102 | 99  | 96  | 99  | 96  | 94  |  | 96  | 94  | 92  |  | 93  |
| 3   | 104 | 98  | 93  | 89  | 102 | 96  | 92  | 88  | 94  | 90  | 87  |  | 91  | 88  | 86  |  | 89  |
| 4   | 99  | 92  | 87  | 83  | 97  | 91  | 86  | 82  | 89  | 85  | 81  |  | 87  | 83  | 80  |  | 85  |
| 5   | 94  | 87  | 81  | 77  | 93  | 86  | 81  | 77  | 84  | 80  | 76  |  | 82  | 79  | 76  |  | 81  |
| 6   | 90  | 82  | 77  | 73  | 89  | 81  | 76  | 72  | 80  | 75  | 72  |  | 78  | 74  | 71  |  | 77  |
| 7   | 86  | 78  | 72  | 68  | 85  | 77  | 72  | 68  | 76  | 71  | 68  |  | 75  | 71  | 67  |  | 74  |
| 8   | 83  | 74  | 68  | 65  | 82  | 73  | 68  | 64  | 72  | 68  | 64  |  | 71  | 67  | 64  |  | 70  |
| 9   | 79  | 70  | 65  | 61  | 78  | 70  | 65  | 61  | 69  | 64  | 61  |  | 68  | 64  | 61  |  | 67  |
| 10  | 76  | 67  | 62  | 58  | 75  | 67  | 62  | 58  | 66  | 61  | 58  |  | 65  | 61  | 58  |  | 65  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 597101 |
| 5°  | 583115 |
| 10° | 536018 |
| 15° | 454191 |
| 20° | 352387 |
| 25° | 246329 |
| 30° | 155188 |
| 35° | 91363  |
| 40° | 51697  |
| 45° | 25119  |
| 50° | 8733   |
| 55° | 7073   |
| 60° | 6842   |
| 65° | 6641   |
| 70° | 6411   |
| 75° | 6015   |
| 80° | 5430   |
| 85° | 3522   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 25119 cd/sqm

TEST NUMBER: P1272725

CATALOG NUMBER: P3AS20R459827D010 E3DL1LI

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 245.2  | 15.4      |
| 10°-20°   | 549.4  | 34.6      |
| 20°-30°   | 466.5  | 29.3      |
| 30°-40°   | 222.6  | 14.0      |
| 40°-50°   | 67.0   | 4.2       |
| 50°-60°   | 17.0   | 1.1       |
| 60°-70°   | 12.7   | 0.8       |
| 70°-80°   | 7.5    | 0.5       |
| 80°-90°   | 2.1    | 0.1       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 1261.1 | 79.3      |
| 0°-40°    | 1483.7 | 93.3      |
| 0°-60°    | 1567.7 | 98.6      |
| 0°-90°    | 1590.0 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 1590.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 2723 |      |
| 5°  | 2649 | 245  |
| 15° | 2001 | 549  |
| 25° | 1018 | 467  |
| 35° | 341  | 223  |
| 45° | 81   | 67   |
| 55° | 18   | 17   |
| 65° | 13   | 13   |
| 75° | 7    | 8    |
| 85° | 1    | 2    |
| 90° | 0    |      |

TEST NUMBER: P1272725

CATALOG NUMBER: P3AS20R459827D010 E3DL1LI

**CANDELA DISTRIBUTION (FULL):**

|       | 0°     |
|-------|--------|
| 0°    | 2723.0 |
| 2.5°  | 2705.9 |
| 5°    | 2649.1 |
| 7.5°  | 2550.9 |
| 10°   | 2407.3 |
| 12.5° | 2216.8 |
| 15°   | 2000.7 |
| 17.5° | 1760.3 |
| 20°   | 1510.1 |
| 22.5° | 1255.6 |
| 25°   | 1018.1 |
| 27.5° | 802.0  |
| 30°   | 612.9  |
| 32.5° | 460.7  |
| 35°   | 341.3  |
| 37.5° | 251.7  |
| 40°   | 180.6  |
| 42.5° | 125.1  |
| 45°   | 81.0   |
| 47.5° | 45.5   |
| 50°   | 25.6   |
| 52.5° | 19.9   |
| 55°   | 18.5   |
| 57.5° | 17.1   |
| 60°   | 15.6   |
| 62.5° | 14.2   |
| 65°   | 12.8   |
| 67.5° | 11.4   |
| 70°   | 10.0   |
| 72.5° | 8.5    |
| 75°   | 7.1    |
| 77.5° | 5.7    |
| 80°   | 4.3    |
| 82.5° | 2.8    |
| 85°   | 1.4    |
| 87.5° | 1.4    |
| 90°   | 0.0    |

(END OF REPORT)