

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1272736

Luminaire Tested: P3AS20R459827D010 E3DLP1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1272736
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-25)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R459827D010 E3DLP1H
Description: 3in Adjustable LED luminaire with, R45 optic, 2700K CCT AND, 98CRI , E3DLP1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1025.9 lumens
Efficiency: N/A
Efficacy: 37.4 lumens/watt
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.76
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1272736

CATALOG NUMBER: P3AS20R459827D010 E3DLP1H

Luminous Intensity Polar Plot



TEST NUMBER: P1272736

CATALOG NUMBER: P3AS20R459827D010 E3DLP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	102	95	90	85	100	93	89	85	91	87	83		88	85	82		86
4	96	88	83	78	94	87	82	78	85	81	77		83	79	76		81
5	91	83	77	72	90	82	76	72	80	75	71		78	74	71		77
6	87	78	72	67	85	77	71	67	75	70	66		74	69	66		73
7	83	73	67	63	81	72	67	63	71	66	62		70	65	62		69
8	79	69	63	59	77	68	63	59	67	62	58		66	62	58		65
9	75	65	59	55	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	61	55	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	305611
5°	298634
10°	275479
15°	239547
20°	196787
25°	153106
30°	113055
35°	79558
40°	49664
45°	26887
50°	14567
55°	12501
60°	11227
65°	9599
70°	8207
75°	8472
80°	7198
85°	7045

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 26887 cd/sqm

TEST NUMBER: P1272736

CATALOG NUMBER: P3AS20R459827D010 E3DLP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	125.6	12.2
10°-20°	291.7	28.4
20°-30°	289.6	28.2
30°-40°	186.5	18.2
40°-50°	71.8	7.0
50°-60°	29.2	2.8
60°-70°	18.4	1.8
70°-80°	10.0	1.0
80°-90°	3.1	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	706.9	68.9
0°-40°	893.4	87.1
0°-60°	994.5	96.9
0°-90°	1025.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1025.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1394	
5°	1357	126
15°	1055	292
25°	633	290
35°	297	186
45°	87	72
55°	33	29
65°	18	18
75°	10	10
85°	3	3
90°	0	

TEST NUMBER: P1272736

CATALOG NUMBER: P3AS20R459827D010 E3DLP1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1393.7
2.5°	1386.6
5°	1356.7
7.5°	1305.5
10°	1237.2
12.5°	1151.9
15°	1055.2
17.5°	950.0
20°	843.3
22.5°	735.2
25°	632.8
27.5°	536.1
30°	446.5
32.5°	368.3
35°	297.2
37.5°	233.2
40°	173.5
42.5°	125.1
45°	86.7
47.5°	58.3
50°	42.7
52.5°	35.6
55°	32.7
57.5°	28.4
60°	25.6
62.5°	21.3
65°	18.5
67.5°	15.6
70°	12.8
72.5°	11.4
75°	10.0
77.5°	7.1
80°	5.7
82.5°	4.3
85°	2.8
87.5°	1.4
90°	0.0

(END OF REPORT)