

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1273940

Luminaire Tested: P3AS13R159830DE010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1273940
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-1)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R159830DE010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R15 optic, 3000K CCT AND, 98CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 219.0 lumens
Efficiency: N/A
Efficacy: 15.1 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.61
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1273940

CATALOG NUMBER: P3AS13R159830DE010 E3DLP1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1273940

CATALOG NUMBER: P3AS13R159830DE010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	106	111	108	106	104	104	102	101		100	99	98		97
2	108	103	98	95	105	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	93	84	78	74	91	83	78	74	81	77	73		80	76	72		78
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74
7	84	75	69	65	83	74	69	65	73	68	64		72	67	64		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		67
9	77	68	62	58	76	67	62	58	66	61	58		65	61	57		64
10	74	64	59	55	73	64	59	55	63	58	55		62	58	55		62

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	94444
5°	87277
10°	69694
15°	52645
20°	40090
25°	30534
30°	21877
35°	14268
40°	8759
45°	5303
50°	3514
55°	2714
60°	2324
65°	2024
70°	1795
75°	1779
80°	1389
85°	1006

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5303 cd/sqm

TEST NUMBER: P1273940

CATALOG NUMBER: P3AS13R159830DE010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	35.1	16.0
10°-20°	64.8	29.6
20°-30°	57.7	26.3
30°-40°	34.1	15.6
40°-50°	14.0	6.4
50°-60°	6.6	3.0
60°-70°	4.0	1.8
70°-80°	2.1	1.0
80°-90°	0.6	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	157.6	72.0
0°-40°	191.8	87.6
0°-60°	212.3	97.0
0°-90°	219.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	219.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	431	
5°	396	35
15°	232	65
25°	126	58
35°	53	34
45°	17	14
55°	7	7
65°	4	4
75°	2	2
85°	0	1
90°	0	

TEST NUMBER: P1273940

CATALOG NUMBER: P3AS13R159830DE010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	430.7
1°	429.6
2°	426.4
3°	420.0
4°	409.3
5°	396.5
6°	382.7
7°	366.3
8°	349.2
9°	331.8
10°	313.0
12.5°	269.9
15°	231.9
17.5°	199.2
20°	171.8
22.5°	147.6
25°	126.2
27.5°	105.6
30°	86.4
32.5°	69.0
35°	53.3
37.5°	40.9
40°	30.6
42.5°	22.8
45°	17.1
47.5°	13.2
50°	10.3
52.5°	8.5
55°	7.1
57.5°	6.0
60°	5.3
62.5°	4.6
65°	3.9
67.5°	3.6
70°	2.8
72.5°	2.5
75°	2.1
77.5°	1.4
80°	1.1
82.5°	0.7
85°	0.4
87.5°	0.4
90°	0.0

(END OF REPORT)