

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1273967

Luminaire Tested: P3AS13R209830DE010 E3DLD1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1273967
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-6)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R209830DE010 E3DLD1LI
Description: 3in Adjustable LED luminaire with, R20 optic, 3000K CCT AND, 98CRI , E3DLD1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 571.0 lumens
Efficiency: N/A
Efficacy: 39.4 lumens/watt
Spacing Criteria (0/90/45): 0.76 / 0.76 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1273967

CATALOG NUMBER: P3AS13R209830DE010 E3DLD1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1273967

CATALOG NUMBER: P3AS13R209830DE010 E3DLD1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		90
3	100	93	87	82	98	91	86	82	88	84	80		86	82	79		84
4	94	86	79	75	92	85	79	74	82	77	73		80	76	72		78
5	89	80	73	68	87	79	73	68	77	71	67		75	70	67		73
6	84	74	68	63	82	73	67	63	72	66	62		70	65	62		69
7	80	69	63	58	78	69	62	58	67	62	58		66	61	57		65
8	75	65	59	54	74	64	58	54	63	58	54		62	57	53		61
9	72	61	55	50	70	61	55	50	60	54	50		59	54	50		58
10	68	58	51	47	67	57	51	47	56	51	47		56	50	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	141239
5°	137464
10°	126451
15°	111306
20°	95465
25°	80206
30°	64820
35°	49309
40°	35094
45°	23165
50°	14362
55°	9443
60°	8596
65°	7887
70°	7437
75°	6778
80°	6440
85°	5535

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 23165 cd/sqm

TEST NUMBER: P1273967

CATALOG NUMBER: P3AS13R209830DE010 E3DLD1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	57.8	10.1
10°-20°	136.5	23.9
20°-30°	151.5	26.5
30°-40°	115.6	20.2
40°-50°	59.2	10.4
50°-60°	24.3	4.3
60°-70°	15.2	2.7
70°-80°	8.5	1.5
80°-90°	2.5	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	345.8	60.6
0°-40°	461.4	80.8
0°-60°	544.9	95.4
0°-90°	571.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	571.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	644	
5°	624	58
15°	490	137
25°	332	152
35°	184	116
45°	75	59
55°	25	24
65°	15	15
75°	8	9
85°	2	2
90°	0	

TEST NUMBER: P1273967

CATALOG NUMBER: P3AS13R209830DE010 E3DLD1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	644.1
1°	644.8
2°	641.9
3°	638.3
4°	632.5
5°	624.5
6°	615.1
7°	604.9
8°	594.0
9°	581.0
10°	567.9
12.5°	530.2
15°	490.3
17.5°	449.7
20°	409.1
22.5°	368.5
25°	331.5
27.5°	294.5
30°	256.0
32.5°	219.8
35°	184.2
37.5°	153.0
40°	122.6
42.5°	96.5
45°	74.7
47.5°	56.6
50°	42.1
52.5°	31.2
55°	24.7
57.5°	22.5
60°	19.6
62.5°	17.4
65°	15.2
67.5°	13.1
70°	11.6
72.5°	9.4
75°	8.0
77.5°	6.5
80°	5.1
82.5°	3.6
85°	2.2
87.5°	0.7
90°	0.0

(END OF REPORT)