

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1273986

Luminaire Tested: P3AS13R259830DE010 E3DL1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1273986
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-11)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R259830DE010 E3DL1GPH
Description: 3in Adjustable LED luminaire with, R25 optic, 3000K CCT AND, 98CRI , E3DL1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 372.0 lumens
Efficiency: N/A
Efficacy: 25.7 lumens/watt
Spacing Criteria (0/90/45): 0.49 / 0.49 / 0.51
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1273986

CATALOG NUMBER: P3AS13R259830DE010 E3DL1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1273986

CATALOG NUMBER: P3AS13R259830DE010 E3DL1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	110	105	102	99	107	104	101	98	101	98	96		98	96	94		95
3	105	100	96	92	103	98	95	91	96	93	90		94	91	89		91
4	101	95	90	87	99	94	89	86	92	88	85		90	87	84		88
5	97	90	85	82	96	89	85	81	88	84	81		86	83	80		85
6	94	86	81	78	92	86	81	78	84	80	77		83	79	77		82
7	90	83	78	74	89	82	77	74	81	77	74		80	76	73		79
8	87	79	74	71	86	79	74	71	78	74	71		77	73	70		76
9	84	76	71	68	83	76	71	68	75	71	68		74	70	68		73
10	81	73	69	65	80	73	68	65	72	68	65		72	68	65		71

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	238621
5°	222628
10°	178353
15°	121068
20°	73250
25°	42825
30°	24383
35°	13411
40°	7128
45°	3752
50°	2183
55°	1644
60°	1403
65°	1453
70°	1346
75°	1186
80°	884
85°	1006

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 3752 cd/sqm

TEST NUMBER: P1273986

CATALOG NUMBER: P3AS13R259830DE010 E3DL1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	89.8	24.1
10°-20°	146.6	39.4
20°-30°	83.8	22.5
30°-40°	33.1	8.9
40°-50°	10.1	2.7
50°-60°	4.0	1.1
60°-70°	2.7	0.7
70°-80°	1.5	0.4
80°-90°	0.5	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	320.1	86.1
0°-40°	353.2	94.9
0°-60°	367.3	98.7
0°-90°	372.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	372.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1088	
5°	1011	90
15°	533	147
25°	177	84
35°	50	33
45°	12	10
55°	4	4
65°	3	3
75°	1	2
85°	0	1
90°	0	

TEST NUMBER: P1273986

CATALOG NUMBER: P3AS13R259830DE010 E3DL1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1088.2
1°	1086.1
2°	1077.2
3°	1061.5
4°	1039.9
5°	1011.4
6°	978.0
7°	940.3
8°	896.6
9°	851.8
10°	801.0
11°	750.8
12°	695.7
13°	641.3
14°	585.5
15°	533.3
17.5°	413.5
20°	313.9
22.5°	235.7
25°	177.0
27.5°	131.2
30°	96.3
32.5°	69.7
35°	50.1
37.5°	35.6
40°	24.9
42.5°	17.1
45°	12.1
47.5°	8.5
50°	6.4
52.5°	5.0
55°	4.3
57.5°	3.9
60°	3.2
62.5°	2.8
65°	2.8
67.5°	2.5
70°	2.1
72.5°	1.8
75°	1.4
77.5°	1.1
80°	0.7
82.5°	0.7
85°	0.4
87.5°	0.4



TEST NUMBER: P1273986

CATALOG NUMBER: P3AS13R259830DE010 E3DL1GPH

CANDELA DISTRIBUTION (continued):



(END OF REPORT)