

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1274418

Luminaire Tested: P3AS17R409830DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1274418
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-12)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R409830DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R40 optic, 3000K CCT AND, 98CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1646.1 lumens
Efficiency: N/A
Efficacy: 80.7 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 20.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1274418

CATALOG NUMBER: P3AS17R409830DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1274418

CATALOG NUMBER: P3AS17R409830DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		96
3	107	102	98	95	105	100	97	94	98	95	93		96	93	91		93
4	103	97	93	90	101	96	92	89	94	91	88		92	89	87		90
5	99	93	89	85	98	92	88	85	91	87	84		89	86	84		88
6	96	89	85	81	95	89	84	81	87	83	81		86	83	80		85
7	93	86	81	78	92	85	81	78	84	80	77		83	80	77		82
8	90	83	78	75	89	82	78	75	81	77	75		80	77	74		79
9	87	80	75	72	86	79	75	72	78	75	72		78	74	72		77
10	84	77	72	70	83	77	72	69	76	72	69		75	72	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	839012
5°	832950
10°	811141
15°	724567
20°	480452
25°	179986
30°	48159
35°	18819
40°	6756
45°	3225
50°	989
55°	459
60°	263
65°	311
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3225 cd/sqm

TEST NUMBER: P1274418

CATALOG NUMBER: P3AS17R409830DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	357.1	21.7
10°-20°	845.7	51.4
20°-30°	383.5	23.3
30°-40°	49.7	3.0
40°-50°	8.6	0.5
50°-60°	1.0	0.1
60°-70°	0.4	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1586.3	96.4
0°-40°	1636.0	99.4
0°-60°	1645.7	100.0
0°-90°	1646.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1646.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3826	
5°	3784	357
15°	3192	846
25°	744	384
35°	70	50
45°	10	9
55°	1	1
65°	1	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1274418

CATALOG NUMBER: P3AS17R409830DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	3826.2
1°	3823.9
2°	3818.1
3°	3809.5
4°	3798.5
5°	3784.1
6°	3767.4
7°	3746.6
8°	3721.3
9°	3686.7
10°	3642.9
11°	3591.6
12°	3523.1
13°	3438.4
14°	3327.7
15°	3191.7
16°	3018.3
17°	2820.6
18°	2583.2
19°	2332.6
20°	2058.9
21°	1785.2
22°	1515.5
23°	1247.0
24°	983.0
25°	743.9
26°	550.9
27°	403.4
28°	303.1
29°	235.7
30°	190.2
31°	157.3
32°	131.4
32.5°	119.9
33°	108.3
34°	88.2
35°	70.3
36°	55.3
37°	43.8
37.5°	39.2
38°	34.6
39°	28.8
40°	23.6
42.5°	15.6
45°	10.4

TEST NUMBER: P1274418

CATALOG NUMBER: P3AS17R409830DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	6.3
50°	2.9
52.5°	1.2
55°	1.2
57.5°	0.6
60°	0.6
62.5°	0.6
65°	0.6
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)