

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1274570

Luminaire Tested: P3AS17R659830DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1274570
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-42)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R659830DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R65 optic, 3000K CCT AND, 98CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 454.0 lumens
Efficiency: N/A
Efficacy: 22.3 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 20.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1274570

CATALOG NUMBER: P3AS17R659830DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1274570

CATALOG NUMBER: P3AS17R659830DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	80783
5°	79705
10°	77042
15°	72645
20°	66996
25°	60826
30°	53882
35°	45829
40°	36468
45°	25739
50°	14942
55°	8143
60°	7587
65°	6901
70°	6283
75°	5846
80°	5051
85°	4277

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 25739 cd/sqm

TEST NUMBER: P1274570

CATALOG NUMBER: P3AS17R659830DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	34.1	7.5
10°-20°	89.5	19.7
20°-30°	115.1	25.3
30°-40°	106.4	23.4
40°-50°	64.2	14.1
50°-60°	21.9	4.8
60°-70°	13.2	2.9
70°-80°	7.4	1.6
80°-90°	2.1	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	238.6	52.6
0°-40°	345.1	76.0
0°-60°	431.2	95.0
0°-90°	454.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	454.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	368	
5°	362	34
15°	320	90
25°	251	115
35°	171	106
45°	83	64
55°	21	22
65°	13	13
75°	7	7
85°	2	2
90°	0	

TEST NUMBER: P1274570

CATALOG NUMBER: P3AS17R659830DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	368.4
2.5°	366.7
5°	362.1
7.5°	355.2
10°	346.0
12.5°	334.4
15°	320.0
17.5°	304.4
20°	287.1
22.5°	269.3
25°	251.4
27.5°	232.4
30°	212.8
32.5°	193.2
35°	171.2
37.5°	149.9
40°	127.4
42.5°	104.9
45°	83.0
47.5°	62.8
50°	43.8
52.5°	27.7
55°	21.3
57.5°	19.0
60°	17.3
62.5°	15.0
65°	13.3
67.5°	11.5
70°	9.8
72.5°	8.6
75°	6.9
77.5°	5.8
80°	4.0
82.5°	2.9
85°	1.7
87.5°	1.2
90°	0.0

(END OF REPORT)