

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1274676

Luminaire Tested: P3AS20R259830D010 E3DL1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1274676
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-11)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R259830D010 E3DL1GPH
Description: 3in Adjustable LED luminaire with, R25 optic, 3000K CCT AND, 98CRI , E3DL1GPH TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 783.9 lumens
Efficiency: N/A
Efficacy: 28.6 lumens/watt
Spacing Criteria (0/90/45): 0.49 / 0.49 / 0.51
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1274676
CATALOG NUMBER: P3AS20R259830D010 E3DL1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P1274676

CATALOG NUMBER: P3AS20R259830D010 E3DL1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95	95	95	95
2	110	105	102	99	107	104	101	98	101	98	96	98	96	94	95	93	92	90	90	90	90
3	105	100	96	92	103	98	95	91	96	93	90	94	91	89	91	89	87	86	86	86	86
4	101	95	90	87	99	94	89	86	92	88	85	90	87	84	88	85	83	82	82	82	82
5	97	90	85	82	96	89	85	81	88	84	81	86	83	80	85	82	79	78	78	78	78
6	94	86	81	78	92	86	81	78	84	80	77	83	79	77	82	78	76	75	75	75	75
7	90	83	78	74	89	82	77	74	81	77	74	80	76	73	79	75	73	72	72	72	72
8	87	79	74	71	86	79	74	71	78	74	71	77	73	70	76	73	70	69	69	69	69
9	84	76	71	68	83	76	71	68	75	71	68	74	70	68	73	70	67	66	66	66	66
10	81	73	69	65	80	73	68	65	72	68	65	72	68	65	71	67	65	64	64	64	64

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	502898
5°	469204
10°	375856
15°	255143
20°	154387
25°	90271
30°	51400
35°	28268
40°	15000
45°	7908
50°	4605
55°	3441
60°	2938
65°	3113
70°	2885
75°	2542
80°	1894
85°	1761

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 7908 cd/sqm



TEST NUMBER: P1274676
 CATALOG NUMBER: P3AS20R259830D010 E3DL1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	189.2	24.1
10°-20°	309.0	39.4
20°-30°	176.6	22.5
30°-40°	69.7	8.9
40°-50°	21.4	2.7
50°-60°	8.4	1.1
60°-70°	5.6	0.7
70°-80°	3.1	0.4
80°-90°	1.0	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	674.7	86.1
0°-40°	744.4	95.0
0°-60°	774.2	98.8
0°-90°	783.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	783.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2293	
5°	2132	189
15°	1124	309
25°	373	177
35°	106	70
45°	26	21
55°	9	8
65°	6	6
75°	3	3
85°	1	1
90°	0	



TEST NUMBER: P1274676
CATALOG NUMBER: P3AS20R259830D010 E3DL1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	2293.4
1°	2288.9
2°	2270.2
3°	2237.2
4°	2191.5
5°	2131.6
6°	2061.2
7°	1981.8
8°	1889.6
9°	1795.2
10°	1688.0
11°	1582.4
12°	1466.3
13°	1351.6
14°	1234.0
15°	1123.9
17.5°	871.4
20°	661.6
22.5°	496.7
25°	373.1
27.5°	276.5
30°	203.0
32.5°	146.9
35°	105.6
37.5°	74.9
40°	52.4
42.5°	36.0
45°	25.5
47.5°	18.0
50°	13.5
52.5°	10.5
55°	9.0
57.5°	8.2
60°	6.7
62.5°	6.0
65°	6.0
67.5°	5.2
70°	4.5
72.5°	3.7
75°	3.0
77.5°	2.2
80°	1.5
82.5°	1.5
85°	0.7
87.5°	0.7



TEST NUMBER: P1274676
CATALOG NUMBER: P3AS20R259830D010 E3DL1GPH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)