

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1274846

Luminaire Tested: P3AS20R559830D010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1274846
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R559830D010 E3D1H
Description: 3in Adjustable LED luminaire with, R55 optic, 3000K CCT AND, 98CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1970.9 lumens
Efficiency: N/A
Efficacy: 71.9 lumens/watt
Spacing Criteria (0/90/45): 0.93 / 0.93 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1274846

CATALOG NUMBER: P3AS20R559830D010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1274846

CATALOG NUMBER: P3AS20R559830D010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	112	109	107	105	105	104	102		102	100	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	104	98	94	90	102	97	93	90	95	91	88		92	89	87		90
4	100	93	88	84	98	92	87	84	90	86	83		88	84	82		86
5	95	88	83	79	94	87	82	78	85	81	78		84	80	77		82
6	91	83	78	74	90	82	77	74	81	76	73		80	76	73		78
7	87	79	73	70	86	78	73	69	77	72	69		76	72	69		75
8	83	75	69	66	82	74	69	66	73	69	65		72	68	65		71
9	80	71	66	62	79	71	66	62	70	65	62		69	65	62		68
10	77	68	62	59	76	67	62	59	67	62	59		66	62	59		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	571577
5°	551330
10°	571043
15°	563000
20°	521055
25°	421403
30°	252545
35°	85581
40°	23587
45°	10451
50°	3070
55°	573
60°	307
65°	363
70°	449
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10451 cd/sqm

TEST NUMBER: P1274846

CATALOG NUMBER: P3AS20R559830D010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	242.3	12.3
10°-20°	690.5	35.0
20°-30°	767.5	38.9
30°-40°	238.9	12.1
40°-50°	28.7	1.5
50°-60°	2.2	0.1
60°-70°	0.7	0.0
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1700.3	86.3
0°-40°	1939.3	98.4
0°-60°	1970.2	100.0
0°-90°	1970.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1970.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2607	
5°	2505	242
15°	2480	690
25°	1742	768
35°	320	239
45°	34	29
55°	2	2
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1274846

CATALOG NUMBER: P3AS20R559830D010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	2606.6
1°	2596.8
2°	2571.4
3°	2539.9
4°	2511.5
5°	2504.7
6°	2512.2
7°	2527.9
8°	2545.9
9°	2560.1
10°	2564.6
11°	2561.6
12°	2549.6
13°	2530.9
14°	2509.2
15°	2480.0
16°	2446.3
17°	2403.6
18°	2355.7
19°	2298.1
20°	2232.9
21°	2158.8
22°	2071.2
23°	1974.6
24°	1863.8
25°	1741.7
26°	1607.7
27°	1465.4
28°	1313.4
29°	1156.9
30°	997.4
31°	837.2
32°	680.7
32.5°	611.0
33°	539.1
34°	417.1
35°	319.7
36°	243.4
37°	180.5
37.5°	154.3
38°	134.0
39°	101.8
40°	82.4
42.5°	52.4
45°	33.7

TEST NUMBER: P1274846

CATALOG NUMBER: P3AS20R559830D010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	20.2
50°	9.0
52.5°	3.0
55°	1.5
57.5°	0.7
60°	0.7
62.5°	0.7
65°	0.7
67.5°	0.7
70°	0.7
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)