

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1274963

Luminaire Tested: P3AS02R159835DE010 E3DL1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1274963
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-3)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R159835DE010 E3DL1GPH
Description: 3in Adjustable LED luminaire with, R15 optic, 3500K CCT AND, 98CRI , E3DL1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 95.0 lumens
Efficiency: N/A
Efficacy: 26.4 lumens/watt
Spacing Criteria (0/90/45): 0.4 / 0.4 / 0.43
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1274963

CATALOG NUMBER: P3AS02R159835DE010 E3DL1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1274963

CATALOG NUMBER: P3AS02R159835DE010 E3DL1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99	98	97	95
2	110	106	103	100	108	104	101	99	101	99	97		98	96	95		96	94	93	91
3	106	101	97	93	104	99	96	93	97	94	91		94	92	90		92	90	88	87
4	102	96	92	88	100	95	91	88	93	89	87		91	88	86		89	87	85	83
5	98	92	87	84	97	91	87	83	89	85	83		88	84	82		86	83	81	80
6	95	88	83	80	94	87	83	80	86	82	79		85	81	79		83	80	78	77
7	92	85	80	77	91	84	80	76	83	79	76		82	78	76		81	78	75	74
8	89	81	77	74	88	81	77	73	80	76	73		79	75	73		78	75	73	72
9	86	79	74	71	85	78	74	71	77	73	71		77	73	70		76	73	70	69
10	84	76	71	68	83	76	71	68	75	71	68		74	71	68		74	70	68	67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	81156
5°	72045
10°	50032
15°	29580
20°	16848
25°	9630
30°	5317
35°	2838
40°	1574
45°	837
50°	546
55°	421
60°	351
65°	311
70°	321
75°	339
80°	253
85°	252

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 837 cd/sqm

TEST NUMBER: P1274963

CATALOG NUMBER: P3AS02R159835DE010 E3DL1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	27.8	29.3
10°-20°	36.7	38.7
20°-30°	18.9	19.9
30°-40°	7.1	7.5
40°-50°	2.3	2.4
50°-60°	1.0	1.1
60°-70°	0.6	0.6
70°-80°	0.4	0.4
80°-90°	0.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	83.5	87.9
0°-40°	90.6	95.3
0°-60°	93.9	98.8
0°-90°	95.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	95.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	370	
5°	327	28
15°	130	37
25°	40	19
35°	11	7
45°	3	2
55°	1	1
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1274963

CATALOG NUMBER: P3AS02R159835DE010 E3DL1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	370.1
1°	369.4
2°	364.5
3°	355.3
4°	343.1
5°	327.3
6°	309.3
7°	289.7
8°	267.8
9°	246.2
10°	224.7
12.5°	172.9
15°	130.3
17.5°	97.6
20°	72.2
22.5°	53.9
25°	39.8
27.5°	29.0
30°	21.0
32.5°	14.9
35°	10.6
37.5°	7.6
40°	5.5
42.5°	3.9
45°	2.7
47.5°	2.0
50°	1.6
52.5°	1.3
55°	1.1
57.5°	0.9
60°	0.8
62.5°	0.7
65°	0.6
67.5°	0.5
70°	0.5
72.5°	0.5
75°	0.4
77.5°	0.3
80°	0.2
82.5°	0.2
85°	0.1
87.5°	0.0
90°	0.0

(END OF REPORT)