

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1275099

Luminaire Tested: P3AS02R359835DE010 E3PH1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1275099
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-5)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R359835DE010 E3PH1MW
Description: 3in Adjustable LED luminaire with, R35 optic, 3500K CCT AND, 98CRI , E3PH1MW TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 217.0 lumens
Efficiency: N/A
Efficacy: 60.3 lumens/watt
Spacing Criteria (0/90/45): 0.57 / 0.56 / 0.51
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1275099
CATALOG NUMBER: P3AS02R359835DE010 E3PH1MW

Luminous Intensity Polar Plot





TEST NUMBER: P1275099

CATALOG NUMBER: P3AS02R359835DE010 E3PH1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98	97
2	111	108	105	102	109	106	103	101	103	101	99	100	98	97	97	96	95	93
3	108	103	100	97	106	102	99	96	99	97	94	97	95	93	95	93	92	90
4	104	99	95	92	103	98	94	92	96	93	91	94	92	90	93	90	89	87
5	101	95	91	88	100	95	91	88	93	90	87	92	89	87	90	88	86	85
6	98	92	88	85	97	91	88	85	90	87	84	89	86	84	88	85	83	82
7	96	89	85	82	94	89	85	82	87	84	81	86	83	81	85	83	81	80
8	93	86	82	79	92	86	82	79	85	81	79	84	81	79	83	80	78	77
9	90	84	80	77	89	83	79	77	82	79	76	82	79	76	81	78	76	75
10	88	81	77	75	87	81	77	74	80	77	74	80	76	74	79	76	74	73

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	156764	156764	156764
5°	154083	153753	153422
10°	141213	136960	133643
15°	101113	97889	96709
20°	46881	48491	50194
25°	11130	15823	16501
30°	3266	3747	4203
35°	750	1205	1098
40°	172	315	200
45°	62	62	62
50°	68	0	68
55°	0	0	0
60°	0	0	0
65°	0	0	0
70°	0	0	0
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 52.5°
 Luminance: 72 cd/sqm



TEST NUMBER: P1275099
 CATALOG NUMBER: P3AS02R359835DE010 E3PH1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	64.2	29.6
10°-20°	114.7	52.9
20°-30°	34.5	15.9
30°-40°	3.3	1.5
40°-50°	0.2	0.1
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	213.5	98.4
0°-40°	216.8	99.9
0°-60°	217.0	100.0
0°-90°	217.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	217.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	715	715	715	715	715	
5°	700	700	698	698	697	65
15°	445	442	431	429	426	118
25°	46	51	65	68	68	30
35°	3	4	4	5	4	3
45°	0	0	0	0	0	0
55°	0	0	0	0	0	0
65°	0	0	0	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P1275099

CATALOG NUMBER: P3AS02R359835DE010 E3PH1MW

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	714.9	714.9	714.9	714.9	714.9
1°	714.6	714.6	714.2	714.2	713.4
2°	712.9	713.1	712.3	712.1	711.6
3°	710.3	709.7	709.7	709.3	709.0
4°	706.2	705.0	704.7	704.8	704.1
5°	700.0	699.8	698.5	697.6	697.0
6°	693.3	691.9	689.1	686.7	686.2
7°	683.2	680.4	677.9	672.9	672.1
8°	670.8	666.3	661.1	654.0	653.6
9°	655.7	648.4	641.1	631.6	628.2
10°	634.2	627.5	615.1	606.7	600.2
11°	607.5	599.1	584.7	574.6	569.1
12°	577.2	569.3	552.5	543.4	535.7
13°	538.3	531.8	516.1	506.0	500.0
14°	493.3	488.4	473.4	469.0	466.9
15°	445.4	442.0	431.2	429.3	426.0
17.5°	327.8	322.2	316.1	317.2	318.3
20°	200.9	208.8	207.8	212.0	215.1
22.5°	100.2	110.3	122.1	129.2	132.7
25°	46.0	50.7	65.4	68.2	68.2
27.5°	23.2	24.3	30.8	31.4	32.9
30°	12.9	13.8	14.8	16.4	16.6
32.5°	6.5	7.7	8.0	9.0	8.6
35°	2.8	3.7	4.5	4.9	4.1
37.5°	1.3	1.7	2.4	2.2	1.7
40°	0.6	0.7	1.1	0.9	0.7
42.5°	0.4	0.4	0.6	0.4	0.4
45°	0.2	0.2	0.2	0.2	0.2
47.5°	0.2	0.2	0.0	0.2	0.2
50°	0.2	0.0	0.0	0.0	0.2
52.5°	0.2	0.0	0.0	0.0	0.2
55°	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P1275099
CATALOG NUMBER: P3AS02R359835DE010 E3PH1MW

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)