

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1275110

Luminaire Tested: P3AS02R409835DE010 E3D1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1275110
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-24)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R409835DE010 E3D1MW
Description: 3in Adjustable LED luminaire with, R40 optic, 3500K CCT AND, 98CRI , E3D1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 262.1 lumens
Efficiency: N/A
Efficacy: 72.8 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.59
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1275110

CATALOG NUMBER: P3AS02R409835DE010 E3D1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1275110

CATALOG NUMBER: P3AS02R409835DE010 E3D1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					30					10					0
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	115	112	110	109		112	110	109	107		106	105	104		103	102	101		99	98	98
2	111	107	104	101		109	105	102	100		102	100	98		99	97	96		96	95	94
3	107	102	98	95		105	100	97	94		98	95	93		96	93	91		94	92	90
4	103	97	93	90		101	96	92	89		94	91	88		92	90	87		91	88	86
5	100	93	89	86		98	92	88	85		91	87	85		89	86	84		88	85	83
6	96	90	85	82		95	89	85	82		88	84	81		86	83	81		85	82	80
7	93	86	82	79		92	86	81	78		84	81	78		83	80	78		82	79	77
8	90	83	79	75		89	83	78	75		82	78	75		81	77	75		80	77	74
9	87	80	76	73		86	80	75	73		79	75	72		78	75	72		77	74	72
10	85	77	73	70		84	77	73	70		76	73	70		76	72	70		75	72	70

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	137949
5°	137288
10°	132819
15°	117504
20°	76657
25°	27147
30°	5748
35°	1901
40°	687
45°	217
50°	205
55°	229
60°	175
65°	208
70°	128
75°	169
80°	253
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 82.5°

Luminance: 336 cd/sqm

TEST NUMBER: P1275110

CATALOG NUMBER: P3AS02R409835DE010 E3D1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	58.7	22.4
10°-20°	136.7	52.1
20°-30°	59.3	22.6
30°-40°	5.5	2.1
40°-50°	0.8	0.3
50°-60°	0.5	0.2
60°-70°	0.4	0.1
70°-80°	0.2	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	254.7	97.2
0°-40°	260.1	99.3
0°-60°	261.4	99.7
0°-90°	262.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	262.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	629	
5°	624	59
15°	518	137
25°	112	59
35°	7	5
45°	1	1
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1275110

CATALOG NUMBER: P3AS02R409835DE010 E3D1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	629.1
2.5°	628.4
5°	623.7
7.5°	613.8
10°	596.5
12.5°	567.2
15°	517.6
17.5°	435.4
20°	328.5
22.5°	213.3
25°	112.2
27.5°	48.3
30°	22.7
32.5°	12.3
35°	7.1
37.5°	4.3
40°	2.4
42.5°	1.3
45°	0.7
47.5°	0.6
50°	0.6
52.5°	0.6
55°	0.6
57.5°	0.6
60°	0.4
62.5°	0.4
65°	0.4
67.5°	0.4
70°	0.2
72.5°	0.2
75°	0.2
77.5°	0.2
80°	0.2
82.5°	0.2
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)