

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1275231

Luminaire Tested: P3AS02R609835DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1275231
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R609835DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R60 optic, 3500K CCT AND, 98CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 75.0 lumens
Efficiency: N/A
Efficacy: 20.8 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1275231

CATALOG NUMBER: P3AS02R609835DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1275231

CATALOG NUMBER: P3AS02R609835DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		57
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	13310
5°	13163
10°	12714
15°	12009
20°	11061
25°	10017
30°	8887
35°	7602
40°	6040
45°	4249
50°	2559
55°	1300
60°	1228
65°	1141
70°	1026
75°	1017
80°	884
85°	755

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4249 cd/sqm

TEST NUMBER: P1275231

CATALOG NUMBER: P3AS02R609835DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	5.6	7.5
10°-20°	14.8	19.7
20°-30°	19.0	25.3
30°-40°	17.6	23.5
40°-50°	10.7	14.3
50°-60°	3.6	4.8
60°-70°	2.2	2.9
70°-80°	1.2	1.6
80°-90°	0.4	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	39.4	52.5
0°-40°	57.0	75.9
0°-60°	71.3	95.0
0°-90°	75.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	75.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	61	
5°	60	6
15°	53	15
25°	41	19
35°	28	18
45°	14	11
55°	3	4
65°	2	2
75°	1	1
85°	0	0
90°	0	

TEST NUMBER: P1275231

CATALOG NUMBER: P3AS02R609835DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	60.7
2.5°	60.4
5°	59.8
7.5°	58.6
10°	57.1
12.5°	55.2
15°	52.9
17.5°	50.2
20°	47.4
22.5°	44.4
25°	41.4
27.5°	38.3
30°	35.1
32.5°	32.0
35°	28.4
37.5°	24.7
40°	21.1
42.5°	17.4
45°	13.7
47.5°	10.7
50°	7.5
52.5°	4.5
55°	3.4
57.5°	3.1
60°	2.8
62.5°	2.5
65°	2.2
67.5°	1.9
70°	1.6
72.5°	1.4
75°	1.2
77.5°	0.9
80°	0.7
82.5°	0.5
85°	0.3
87.5°	0.2
90°	0.0

(END OF REPORT)