

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1275252

Luminaire Tested: P3AS02R659835DE010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1275252
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R659835DE010 E3D1WH
Description: 3in Adjustable LED luminaire with, R65 optic, 3500K CCT AND, 98CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 223.0 lumens
Efficiency: N/A
Efficacy: 62.0 lumens/watt
Spacing Criteria (0/90/45): 0.92 / 0.92 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1275252

CATALOG NUMBER: P3AS02R659835DE010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1275252

CATALOG NUMBER: P3AS02R659835DE010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	95	91	87	93	89	86		90	87	85		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75
7	84	75	70	65	83	75	69	65	73	69	65		72	68	65		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		67
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	59754
5°	55492
10°	53662
15°	51714
20°	47814
25°	43551
30°	33651
35°	19515
40°	7729
45°	3287
50°	785
55°	115
60°	88
65°	52
70°	64
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3287 cd/sqm

TEST NUMBER: P1275252

CATALOG NUMBER: P3AS02R659835DE010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	23.8	10.7
10°-20°	63.5	28.5
20°-30°	80.3	36.0
30°-40°	45.8	20.5
40°-50°	9.1	4.1
50°-60°	0.5	0.2
60°-70°	0.1	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	167.6	75.1
0°-40°	213.3	95.6
0°-60°	222.9	99.9
0°-90°	223.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	223.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	272	
5°	252	24
15°	228	63
25°	180	80
35°	73	46
45°	11	9
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1275252

CATALOG NUMBER: P3AS02R659835DE010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	272.5
1°	270.5
2°	266.1
3°	261.0
4°	255.9
5°	252.1
6°	249.2
7°	246.9
8°	244.9
9°	242.9
10°	241.0
11°	238.9
12°	236.7
13°	234.0
14°	231.2
15°	227.8
16°	223.7
17°	219.3
18°	214.6
19°	209.5
20°	204.9
21°	200.1
22°	195.8
23°	191.3
24°	186.1
25°	180.0
26°	172.8
27°	164.1
28°	154.3
29°	143.8
30°	132.9
31°	120.9
32°	109.0
32.5°	102.8
33°	96.9
34°	84.8
35°	72.9
36°	61.9
37°	51.0
37.5°	45.4
38°	40.9
39°	33.1
40°	27.0
42.5°	16.7
45°	10.6



TEST NUMBER: P1275252
CATALOG NUMBER: P3AS02R659835DE010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	6.2
50°	2.3
52.5°	0.5
55°	0.3
57.5°	0.2
60°	0.2
62.5°	0.2
65°	0.1
67.5°	0.1
70°	0.1
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)