

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1275655

Luminaire Tested: P3AS09R159835DE010 E3DL1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1275655
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-3)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R159835DE010 E3DL1LI
Description: 3in Adjustable LED luminaire with, R15 optic, 3500K CCT AND, 98CRI , E3DL1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 592.0 lumens
Efficiency: N/A
Efficacy: 53.8 lumens/watt
Spacing Criteria (0/90/45): 0.4 / 0.4 / 0.43
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1275655

CATALOG NUMBER: P3AS09R159835DE010 E3DL1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1275655

CATALOG NUMBER: P3AS09R159835DE010 E3DL1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	110	106	103	100	108	104	101	99	101	99	97		98	96	95		96
3	106	101	97	93	104	99	96	93	97	94	91		94	92	90		92
4	102	96	92	88	100	95	91	88	93	89	87		91	88	86		89
5	98	92	87	84	97	91	87	83	89	85	83		88	84	82		86
6	95	88	83	80	94	87	83	80	86	82	79		85	81	79		83
7	92	85	80	77	91	84	80	76	83	79	76		82	78	76		81
8	89	81	77	74	88	81	77	73	80	76	73		79	75	73		78
9	86	79	74	71	85	78	74	71	77	73	71		77	73	70		76
10	84	76	71	68	83	76	71	68	75	71	68		74	71	68		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	505727
5°	448909
10°	311751
15°	184360
20°	105009
25°	60028
30°	33220
35°	17721
40°	9790
45°	5303
50°	3309
55°	2600
60°	2237
65°	2075
70°	1859
75°	1949
80°	1389
85°	1510

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 5303 cd/sqm

TEST NUMBER: P1275655

CATALOG NUMBER: P3AS09R159835DE010 E3DL1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	173.4	29.3
10°-20°	228.9	38.7
20°-30°	117.9	19.9
30°-40°	44.3	7.5
40°-50°	14.5	2.4
50°-60°	6.2	1.1
60°-70°	4.0	0.7
70°-80°	2.3	0.4
80°-90°	0.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	520.1	87.9
0°-40°	564.4	95.3
0°-60°	585.1	98.8
0°-90°	592.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	592.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2306	
5°	2039	173
15°	812	229
25°	248	118
35°	66	44
45°	17	14
55°	7	6
65°	4	4
75°	2	2
85°	1	1
90°	0	

TEST NUMBER: P1275655

CATALOG NUMBER: P3AS09R159835DE010 E3DL1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	2306.3
1°	2301.7
2°	2271.5
3°	2213.9
4°	2138.0
5°	2039.4
6°	1927.6
7°	1805.0
8°	1668.7
9°	1534.1
10°	1400.1
12.5°	1077.3
15°	812.1
17.5°	607.9
20°	450.0
22.5°	335.9
25°	248.1
27.5°	180.8
30°	131.2
32.5°	93.0
35°	66.2
37.5°	47.3
40°	34.2
42.5°	24.5
45°	17.1
47.5°	12.5
50°	9.7
52.5°	8.0
55°	6.8
57.5°	5.7
60°	5.1
62.5°	4.6
65°	4.0
67.5°	3.4
70°	2.9
72.5°	2.9
75°	2.3
77.5°	1.7
80°	1.1
82.5°	1.1
85°	0.6
87.5°	0.0
90°	0.0

(END OF REPORT)