

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1275834

Luminaire Tested: P3AS09R459835DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1275834
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-26)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R459835DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R45 optic, 3500K CCT AND, 98CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 242.9 lumens
Efficiency: N/A
Efficacy: 22.1 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.92
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1275834

CATALOG NUMBER: P3AS09R459835DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1275834

CATALOG NUMBER: P3AS09R459835DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	97	96		96
2	106	100	95	91	103	98	94	90	95	91	88		92	89	86		89
3	99	92	86	82	97	91	85	81	88	83	80		85	81	78		83
4	94	85	78	74	92	84	78	73	81	76	72		79	75	71		77
5	88	79	72	67	86	78	71	67	76	70	66		74	69	65		72
6	83	73	66	61	81	72	66	61	71	65	61		69	64	60		68
7	78	68	61	57	77	67	61	56	66	60	56		65	60	56		64
8	74	64	57	52	73	63	57	52	62	56	52		61	56	52		60
9	70	60	53	49	69	59	53	49	58	52	48		57	52	48		56
10	67	56	50	45	66	56	49	45	55	49	45		54	49	45		53

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	51531
5°	50605
10°	47895
15°	43678
20°	38620
25°	33534
30°	28789
35°	23985
40°	17862
45°	10947
50°	5049
55°	3976
60°	3815
65°	3476
70°	3206
75°	3050
80°	2778
85°	2013

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10947 cd/sqm

TEST NUMBER: P1275834

CATALOG NUMBER: P3AS09R459835DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	21.5	8.8
10°-20°	53.6	22.0
20°-30°	63.6	26.2
30°-40°	55.3	22.8
40°-50°	27.7	11.4
50°-60°	9.6	4.0
60°-70°	6.7	2.8
70°-80°	3.7	1.5
80°-90°	1.1	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	138.7	57.1
0°-40°	194.0	79.8
0°-60°	231.3	95.2
0°-90°	242.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	242.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	235	
5°	230	21
15°	192	54
25°	139	64
35°	90	55
45°	35	28
55°	10	10
65°	7	7
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1275834

CATALOG NUMBER: P3AS09R459835DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	235.0
2.5°	233.8
5°	229.9
7.5°	223.8
10°	215.1
12.5°	204.4
15°	192.4
17.5°	178.9
20°	165.5
22.5°	151.8
25°	138.6
27.5°	126.0
30°	113.7
32.5°	101.9
35°	89.6
37.5°	76.5
40°	62.4
42.5°	48.7
45°	35.3
47.5°	23.2
50°	14.8
52.5°	11.5
55°	10.4
57.5°	9.5
60°	8.7
62.5°	7.8
65°	6.7
67.5°	5.9
70°	5.0
72.5°	4.2
75°	3.6
77.5°	2.8
80°	2.2
82.5°	1.7
85°	0.8
87.5°	0.6
90°	0.0

(END OF REPORT)