

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1275942

Luminaire Tested: P3AS09R659835DE010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1275942
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R659835DE010 E3D1WH
Description: 3in Adjustable LED luminaire with, R65 optic, 3500K CCT AND, 98CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 681.0 lumens
Efficiency: N/A
Efficacy: 61.9 lumens/watt
Spacing Criteria (0/90/45): 0.92 / 0.92 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1275942

CATALOG NUMBER: P3AS09R659835DE010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1275942

CATALOG NUMBER: P3AS09R659835DE010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	95	91	87	93	89	86		90	87	85		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75
7	84	75	70	65	83	75	69	65	73	69	65		72	68	65		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		67
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	182485
5°	169425
10°	163858
15°	157912
20°	145986
25°	133000
30°	102775
35°	59562
40°	23644
45°	10079
50°	2388
55°	306
60°	263
65°	156
70°	192
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10079 cd/sqm

TEST NUMBER: P1275942

CATALOG NUMBER: P3AS09R659835DE010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	72.6	10.7
10°-20°	193.8	28.5
20°-30°	245.3	36.0
30°-40°	139.7	20.5
40°-50°	27.7	4.1
50°-60°	1.4	0.2
60°-70°	0.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	511.7	75.1
0°-40°	651.4	95.6
0°-60°	680.6	99.9
0°-90°	681.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	681.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	832	
5°	770	73
15°	696	194
25°	550	245
35°	222	140
45°	32	28
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1275942

CATALOG NUMBER: P3AS09R659835DE010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	832.2
1°	826.0
2°	812.6
3°	796.9
4°	781.5
5°	769.7
6°	761.1
7°	754.1
8°	747.9
9°	741.8
10°	735.9
11°	729.4
12°	722.7
13°	714.6
14°	705.9
15°	695.6
16°	683.3
17°	669.8
18°	655.3
19°	639.9
20°	625.6
21°	611.0
22°	597.9
23°	584.2
24°	568.2
25°	549.7
26°	527.6
27°	501.0
28°	471.1
29°	439.2
30°	405.9
31°	369.2
32°	332.8
32.5°	314.1
33°	295.9
34°	258.9
35°	222.5
36°	188.9
37°	155.6
37.5°	138.6
38°	124.8
39°	101.0
40°	82.6
42.5°	50.9
45°	32.5



TEST NUMBER: P1275942

CATALOG NUMBER: P3AS09R659835DE010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	19.0
50°	7.0
52.5°	1.4
55°	0.8
57.5°	0.6
60°	0.6
62.5°	0.6
65°	0.3
67.5°	0.3
70°	0.3
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)