

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1275950

Luminaire Tested: P3AS09R659835DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1275950
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-42)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R659835DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R65 optic, 3500K CCT AND, 98CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 220.0 lumens
Efficiency: N/A
Efficacy: 20.0 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1275950

CATALOG NUMBER: P3AS09R659835DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1275950

CATALOG NUMBER: P3AS09R659835DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	39142
5°	38631
10°	37318
15°	35210
20°	32459
25°	29469
30°	26105
35°	22218
40°	17662
45°	12466
50°	7232
55°	3938
60°	3684
65°	3321
70°	3013
75°	2881
80°	2526
85°	2013

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 12466 cd/sqm

TEST NUMBER: P1275950

CATALOG NUMBER: P3AS09R659835DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	16.5	7.5
10°-20°	43.4	19.7
20°-30°	55.8	25.3
30°-40°	51.6	23.4
40°-50°	31.1	14.2
50°-60°	10.6	4.8
60°-70°	6.4	2.9
70°-80°	3.6	1.6
80°-90°	1.0	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	115.6	52.6
0°-40°	167.2	76.0
0°-60°	208.9	95.0
0°-90°	220.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	220.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	178	
5°	176	17
15°	155	43
25°	122	56
35°	83	52
45°	40	31
55°	10	11
65°	6	6
75°	3	4
85°	1	1
90°	0	

TEST NUMBER: P1275950

CATALOG NUMBER: P3AS09R659835DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	178.5
2.5°	177.7
5°	175.5
7.5°	172.1
10°	167.6
12.5°	162.1
15°	155.1
17.5°	147.5
20°	139.1
22.5°	130.5
25°	121.8
27.5°	112.6
30°	103.1
32.5°	93.6
35°	83.0
37.5°	72.6
40°	61.7
42.5°	50.9
45°	40.2
47.5°	30.5
50°	21.2
52.5°	13.4
55°	10.3
57.5°	9.2
60°	8.4
62.5°	7.3
65°	6.4
67.5°	5.6
70°	4.7
72.5°	4.2
75°	3.4
77.5°	2.8
80°	2.0
82.5°	1.4
85°	0.8
87.5°	0.6
90°	0.0

(END OF REPORT)