

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276062

Luminaire Tested: P3AS13R259835DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1276062
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R259835DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R25 optic, 3500K CCT AND, 98CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 298.1 lumens
Efficiency: N/A
Efficacy: 20.6 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1276062

CATALOG NUMBER: P3AS13R259835DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1276062

CATALOG NUMBER: P3AS13R259835DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	70828
5°	69139
10°	64060
15°	57049
20°	49028
25°	41688
30°	34309
35°	26742
40°	19236
45°	12218
50°	7232
55°	4970
60°	4561
65°	4255
70°	3783
75°	3474
80°	3283
85°	2768

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 12218 cd/sqm

TEST NUMBER: P1276062

CATALOG NUMBER: P3AS13R259835DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	29.1	9.8
10°-20°	69.8	23.4
20°-30°	78.8	26.5
30°-40°	62.4	20.9
40°-50°	31.5	10.6
50°-60°	12.6	4.2
60°-70°	8.1	2.7
70°-80°	4.4	1.5
80°-90°	1.3	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	177.7	59.6
0°-40°	240.1	80.6
0°-60°	284.2	95.4
0°-90°	298.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	298.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	323	
5°	314	29
15°	251	70
25°	172	79
35°	100	62
45°	39	31
55°	13	13
65°	8	8
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1276062

CATALOG NUMBER: P3AS13R259835DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	323.0
1°	323.0
2°	321.9
3°	320.0
4°	317.4
5°	314.1
6°	310.0
7°	305.2
8°	300.0
9°	294.0
10°	287.7
11°	280.7
12°	274.0
13°	266.2
14°	258.8
15°	251.3
17.5°	230.5
20°	210.1
22.5°	190.8
25°	172.3
27.5°	154.1
30°	135.5
32.5°	118.1
35°	99.9
37.5°	83.2
40°	67.2
42.5°	52.3
45°	39.4
47.5°	29.3
50°	21.2
52.5°	16.0
55°	13.0
57.5°	11.9
60°	10.4
62.5°	9.3
65°	8.2
67.5°	7.1
70°	5.9
72.5°	5.2
75°	4.1
77.5°	3.3
80°	2.6
82.5°	1.9
85°	1.1
87.5°	0.4



TEST NUMBER: P1276062
CATALOG NUMBER: P3AS13R259835DE010 E3DLD1GPH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)