

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276269

Luminaire Tested: P3AS13R609835DE010 E3DLD1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1276269
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R609835DE010 E3DLD1MW
Description: 3in Adjustable LED luminaire with, R60 optic, 3500K CCT AND, 98CRI , E3DLD1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 624.0 lumens
Efficiency: N/A
Efficacy: 43.0 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1276269

CATALOG NUMBER: P3AS13R609835DE010 E3DLD1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1276269

CATALOG NUMBER: P3AS13R609835DE010 E3DLD1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	110759
5°	109531
10°	105743
15°	99887
20°	92081
25°	83376
30°	74011
35°	63256
40°	50294
45°	35477
50°	21185
55°	10705
60°	10306
65°	9443
70°	8719
75°	8303
80°	7703
85°	5787

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 35477 cd/sqm

TEST NUMBER: P1276269

CATALOG NUMBER: P3AS13R609835DE010 E3DLD1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	46.8	7.5
10°-20°	123.0	19.7
20°-30°	157.9	25.3
30°-40°	146.4	23.5
40°-50°	89.1	14.3
50°-60°	29.7	4.8
60°-70°	18.1	2.9
70°-80°	10.2	1.6
80°-90°	2.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	327.6	52.5
0°-40°	474.0	76.0
0°-60°	592.8	95.0
0°-90°	624.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	624.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	505	
5°	498	47
15°	440	123
25°	345	158
35°	236	146
45°	114	89
55°	28	30
65°	18	18
75°	10	10
85°	2	3
90°	0	

TEST NUMBER: P1276269

CATALOG NUMBER: P3AS13R609835DE010 E3DLD1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	505.1
2.5°	502.9
5°	497.6
7.5°	487.7
10°	474.9
12.5°	459.0
15°	440.0
17.5°	418.1
20°	394.6
22.5°	369.6
25°	344.6
27.5°	318.8
30°	292.3
32.5°	265.8
35°	236.3
37.5°	205.2
40°	175.7
42.5°	144.7
45°	114.4
47.5°	88.6
50°	62.1
52.5°	37.1
55°	28.0
57.5°	25.7
60°	23.5
62.5°	20.4
65°	18.2
67.5°	15.9
70°	13.6
72.5°	11.4
75°	9.8
77.5°	7.6
80°	6.1
82.5°	3.8
85°	2.3
87.5°	1.5
90°	0.0

(END OF REPORT)