

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276313

Luminaire Tested: P3AS13R709835DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1276313
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-17)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R709835DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R70 optic, 3500K CCT AND, 98CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 903.0 lumens
Efficiency: N/A
Efficacy: 62.3 lumens/watt
Spacing Criteria (0/90/45): 1.02 / 1.02 / 1.06
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1276313

CATALOG NUMBER: P3AS13R709835DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1276313

CATALOG NUMBER: P3AS13R709835DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	81		86
4	95	87	81	77	94	86	81	77	84	79	76		82	78	75		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	75	69	64	83	75	69	64	73	68	64		72	67	63		70
7	80	70	64	59	79	70	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	51	47	67	57	51	47	56	51	47		55	50	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	175578
5°	165551
10°	156978
15°	154167
20°	148600
25°	140065
30°	139085
35°	121131
40°	78347
45°	37027
50°	5185
55°	421
60°	307
65°	363
70°	256
75°	339
80°	505
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 37027 cd/sqm

TEST NUMBER: P1276313

CATALOG NUMBER: P3AS13R709835DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	70.2	7.8
10°-20°	190.7	21.1
20°-30°	269.8	29.9
30°-40°	271.1	30.0
40°-50°	97.5	10.8
50°-60°	2.6	0.3
60°-70°	0.6	0.1
70°-80°	0.4	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	530.7	58.8
0°-40°	801.8	88.8
0°-60°	902.0	99.9
0°-90°	903.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	903.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	801	
5°	752	70
15°	679	191
25°	579	270
35°	452	271
45°	119	98
55°	1	3
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1276313

CATALOG NUMBER: P3AS13R709835DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	800.7
1°	798.5
2°	791.4
3°	780.3
4°	766.2
5°	752.1
6°	738.8
7°	728.4
8°	719.1
9°	711.7
10°	705.0
11°	699.5
12°	694.3
13°	689.1
14°	684.3
15°	679.1
16°	672.8
17°	666.1
18°	657.9
19°	647.9
20°	636.8
21°	624.6
22°	612.3
23°	600.4
24°	588.9
25°	578.9
26°	571.9
27°	566.3
28°	561.9
29°	556.7
30°	549.3
31°	538.5
32°	523.3
32.5°	514.8
33°	503.3
34°	480.7
35°	452.5
36°	421.3
37°	386.1
37.5°	369.8
38°	347.5
39°	307.8
40°	273.7
42.5°	189.5
45°	119.4



TEST NUMBER: P1276313

CATALOG NUMBER: P3AS13R709835DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	64.2
50°	15.2
52.5°	1.9
55°	1.1
57.5°	1.1
60°	0.7
62.5°	0.7
65°	0.7
67.5°	0.4
70°	0.4
72.5°	0.4
75°	0.4
77.5°	0.4
80°	0.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)