

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276564

Luminaire Tested: P3AS17R509835DE010 E3DLP1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1276564
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-29)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R509835DE010 E3DLP1WMH
Description: 3in Adjustable LED luminaire with, R50 optic, 3500K CCT AND, 98CRI , E3DLP1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 906.0 lumens
Efficiency: N/A
Efficacy: 44.4 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 20.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1276564

CATALOG NUMBER: P3AS17R509835DE010 E3DLP1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1276564

CATALOG NUMBER: P3AS17R509835DE010 E3DLP1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	95	89	85	99	93	88	85	91	87	83		88	85	82		86
4	96	88	82	78	94	87	82	78	85	80	77		83	79	76		81
5	91	83	76	72	90	82	76	72	80	75	71		78	74	70		77
6	87	77	71	67	85	77	71	67	75	70	66		74	69	66		72
7	82	73	67	62	81	72	66	62	71	66	62		70	65	61		68
8	78	69	63	58	77	68	62	58	67	62	58		66	61	58		65
9	75	65	59	55	74	64	59	55	63	58	55		63	58	54		62
10	71	61	56	52	70	61	55	52	60	55	51		59	55	51		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	263510
5°	256416
10°	236446
15°	207947
20°	173965
25°	137960
30°	101205
35°	69600
40°	44226
45°	24716
50°	13373
55°	11240
60°	9692
65°	8924
70°	7886
75°	7286
80°	6188
85°	6290

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 24716 cd/sqm

TEST NUMBER: P1276564

CATALOG NUMBER: P3AS17R509835DE010 E3DLP1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	107.9	11.9
10°-20°	253.7	28.0
20°-30°	259.5	28.6
30°-40°	164.6	18.2
40°-50°	65.5	7.2
50°-60°	26.5	2.9
60°-70°	17.0	1.9
70°-80°	8.7	1.0
80°-90°	2.7	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	621.1	68.5
0°-40°	785.6	86.7
0°-60°	877.6	96.9
0°-90°	906.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	906.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1202	
5°	1165	108
15°	916	254
25°	570	259
35°	260	165
45°	80	65
55°	29	27
65°	17	17
75°	9	9
85°	2	3
90°	0	

TEST NUMBER: P1276564

CATALOG NUMBER: P3AS17R509835DE010 E3DLP1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1201.7
2.5°	1193.1
5°	1164.9
7.5°	1120.8
10°	1061.9
12.5°	992.0
15°	916.0
17.5°	832.6
20°	745.5
22.5°	658.5
25°	570.2
27.5°	481.9
30°	399.7
32.5°	326.2
35°	260.0
37.5°	203.6
40°	154.5
42.5°	114.0
45°	79.7
47.5°	54.0
50°	39.2
52.5°	33.1
55°	29.4
57.5°	25.8
60°	22.1
62.5°	19.6
65°	17.2
67.5°	14.7
70°	12.3
72.5°	9.8
75°	8.6
77.5°	6.1
80°	4.9
82.5°	3.7
85°	2.5
87.5°	1.2
90°	0.0

(END OF REPORT)