

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276725

Luminaire Tested: P3AS20R209835D010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1276725
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-6)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R209835D010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R20 optic, 3500K CCT AND, 98CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 615.0 lumens
Efficiency: N/A
Efficacy: 22.4 lumens/watt
Spacing Criteria (0/90/45): 0.76 / 0.76 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1276725

CATALOG NUMBER: P3AS20R209835D010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1276725

CATALOG NUMBER: P3AS20R209835D010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		90
3	100	93	87	82	98	91	86	82	88	84	80		86	82	79		84
4	94	86	79	75	92	85	79	74	82	77	73		80	76	72		78
5	89	80	73	68	87	79	73	68	77	71	67		75	70	67		73
6	84	74	68	63	82	73	67	63	72	66	62		70	65	62		69
7	80	69	63	58	78	69	62	58	67	62	58		66	61	57		65
8	75	65	59	54	74	64	58	54	63	58	54		62	57	53		61
9	72	61	55	50	70	61	55	50	60	54	50		59	54	50		58
10	68	58	51	47	67	57	51	47	56	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	152115
5°	148052
10°	136203
15°	119887
20°	102816
25°	86376
30°	69834
35°	53110
40°	37785
45°	24964
50°	15454
55°	10169
60°	9254
65°	8509
70°	8014
75°	7286
80°	6945
85°	5787

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 24964 cd/sqm

TEST NUMBER: P1276725

CATALOG NUMBER: P3AS20R209835D010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	62.2	10.1
10°-20°	147.0	23.9
20°-30°	163.2	26.5
30°-40°	124.5	20.2
40°-50°	63.7	10.4
50°-60°	26.2	4.3
60°-70°	16.3	2.7
70°-80°	9.2	1.5
80°-90°	2.7	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	372.4	60.6
0°-40°	496.9	80.8
0°-60°	586.8	95.4
0°-90°	615.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	615.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	694	
5°	673	62
15°	528	147
25°	357	163
35°	198	124
45°	80	64
55°	27	26
65°	16	16
75°	9	9
85°	2	3
90°	0	

TEST NUMBER: P1276725

CATALOG NUMBER: P3AS20R209835D010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	693.7
1°	694.5
2°	691.4
3°	687.5
4°	681.2
5°	672.6
6°	662.5
7°	651.5
8°	639.8
9°	625.8
10°	611.7
12.5°	571.1
15°	528.1
17.5°	484.4
20°	440.6
22.5°	396.9
25°	357.0
27.5°	317.2
30°	275.8
32.5°	236.7
35°	198.4
37.5°	164.8
40°	132.0
42.5°	103.9
45°	80.5
47.5°	60.9
50°	45.3
52.5°	33.6
55°	26.6
57.5°	24.2
60°	21.1
62.5°	18.7
65°	16.4
67.5°	14.1
70°	12.5
72.5°	10.2
75°	8.6
77.5°	7.0
80°	5.5
82.5°	3.9
85°	2.3
87.5°	0.8
90°	0.0

(END OF REPORT)