

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276759

Luminaire Tested: P3AS20R259835D010 E3DLP1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1276759
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R259835D010 E3DLP1H
Description: 3in Adjustable LED luminaire with, R25 optic, 3500K CCT AND, 98CRI , E3DLP1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1022.0 lumens
Efficiency: N/A
Efficacy: 37.3 lumens/watt
Spacing Criteria (0/90/45): 0.62 / 0.62 / 0.68
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1276759

CATALOG NUMBER: P3AS20R259835D010 E3DLP1H

Luminous Intensity Polar Plot



TEST NUMBER: P1276759

CATALOG NUMBER: P3AS20R259835D010 E3DLP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	101		100	99	98		97
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92
3	102	95	90	86	100	94	89	86	91	87	84		89	86	83		87
4	97	89	84	79	95	88	83	79	86	81	78		84	80	77		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	84	74	68	64	82	74	68	64	72	67	64		71	67	63		70
8	80	70	65	60	79	70	64	60	69	64	60		68	63	60		67
9	76	67	61	57	75	66	61	57	65	60	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	371045
5°	355975
10°	311840
15°	250671
20°	192587
25°	145726
30°	105307
35°	69948
40°	42422
45°	24716
50°	15761
55°	12807
60°	11183
65°	9910
70°	8142
75°	8133
80°	6061
85°	8051

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 24716 cd/sqm

TEST NUMBER: P1276759

CATALOG NUMBER: P3AS20R259835D010 E3DLP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	147.2	14.4
10°-20°	305.3	29.9
20°-30°	276.1	27.0
30°-40°	165.9	16.2
40°-50°	65.9	6.4
50°-60°	30.4	3.0
60°-70°	18.5	1.8
70°-80°	9.9	1.0
80°-90°	2.8	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	728.7	71.3
0°-40°	894.5	87.5
0°-60°	990.8	96.9
0°-90°	1022.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1022.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1692	
5°	1617	147
15°	1104	305
25°	602	276
35°	261	166
45°	80	66
55°	34	30
65°	19	18
75°	10	10
85°	3	3
90°	0	

TEST NUMBER: P1276759

CATALOG NUMBER: P3AS20R259835D010 E3DLP1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1692.1
1°	1692.1
2°	1684.1
3°	1666.6
4°	1644.3
5°	1617.2
6°	1582.1
7°	1542.3
8°	1496.1
9°	1449.9
10°	1400.5
11°	1343.2
12°	1284.2
13°	1225.2
14°	1166.3
15°	1104.2
17.5°	957.6
20°	825.3
22.5°	705.8
25°	602.3
27.5°	505.1
30°	415.9
32.5°	334.6
35°	261.3
37.5°	199.2
40°	148.2
42.5°	108.3
45°	79.7
47.5°	60.5
50°	46.2
52.5°	38.2
55°	33.5
57.5°	28.7
60°	25.5
62.5°	20.7
65°	19.1
67.5°	15.9
70°	12.7
72.5°	11.2
75°	9.6
77.5°	8.0
80°	4.8
82.5°	3.2
85°	3.2
87.5°	1.6



TEST NUMBER: P1276759
CATALOG NUMBER: P3AS20R259835D010 E3DLP1H

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)