

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276938

Luminaire Tested: P3AS20R559835D010 E3DLP1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1276938
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-33)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R559835D010 E3DLP1WMH
Description: 3in Adjustable LED luminaire with, R55 optic, 3500K CCT AND, 98CRI , E3DLP1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1160.0 lumens
Efficiency: N/A
Efficacy: 42.3 lumens/watt
Spacing Criteria (0/90/45): 0.77 / 0.77 / 0.8
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1276938

CATALOG NUMBER: P3AS20R559835D010 E3DLP1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1276938

CATALOG NUMBER: P3AS20R559835D010 E3DLP1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		97
2	107	102	97	94	105	100	96	93	97	93	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	81		85
4	96	88	82	77	94	87	81	77	84	80	76		82	78	75		80
5	91	82	76	71	89	81	75	71	79	74	70		77	73	70		76
6	86	77	70	66	84	76	70	66	74	69	65		73	68	65		72
7	82	72	66	61	80	71	65	61	70	65	61		69	64	60		68
8	78	68	62	57	76	67	61	57	66	61	57		65	60	57		64
9	74	64	58	54	73	63	58	54	62	57	53		62	57	53		61
10	70	60	55	51	69	60	54	50	59	54	50		58	54	50		58

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	315567
5°	307637
10°	286011
15°	254689
20°	216435
25°	174663
30°	133160
35°	94710
40°	62489
45°	37058
50°	21731
55°	13419
60°	11885
65°	10740
70°	9168
75°	8133
80°	8082
85°	8051

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 37058 cd/sqm

TEST NUMBER: P1276938

CATALOG NUMBER: P3AS20R559835D010 E3DLP1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	129.8	11.2
10°-20°	311.0	26.8
20°-30°	329.4	28.4
30°-40°	222.6	19.2
40°-50°	97.5	8.4
50°-60°	34.9	3.0
60°-70°	20.5	1.8
70°-80°	10.7	0.9
80°-90°	3.5	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	770.2	66.4
0°-40°	992.8	85.6
0°-60°	1125.3	97.0
0°-90°	1160.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1160.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1439	
5°	1398	130
15°	1122	311
25°	722	329
35°	354	223
45°	120	98
55°	35	35
65°	21	20
75°	10	11
85°	3	3
90°	0	

TEST NUMBER: P1276938

CATALOG NUMBER: P3AS20R559835D010 E3DLP1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1439.1
2.5°	1427.9
5°	1397.6
7.5°	1348.2
10°	1284.5
12.5°	1208.0
15°	1121.9
17.5°	1026.3
20°	927.5
22.5°	823.9
25°	721.9
27.5°	621.5
30°	525.9
32.5°	435.1
35°	353.8
37.5°	280.5
40°	218.3
42.5°	164.1
45°	119.5
47.5°	87.6
50°	63.7
52.5°	44.6
55°	35.1
57.5°	31.9
60°	27.1
62.5°	23.9
65°	20.7
67.5°	17.5
70°	14.3
72.5°	12.7
75°	9.6
77.5°	8.0
80°	6.4
82.5°	4.8
85°	3.2
87.5°	1.6
90°	0.0

(END OF REPORT)