

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276948

Luminaire Tested: P3AS20R609835D010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1276948
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R609835D010 E3D1WH
Description: 3in Adjustable LED luminaire with, R60 optic, 3500K CCT AND, 98CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1910.0 lumens
Efficiency: N/A
Efficacy: 69.7 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1276948

CATALOG NUMBER: P3AS20R609835D010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1276948

CATALOG NUMBER: P3AS20R609835D010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	96	91	88	93	89	86		91	87	85		88
4	98	91	85	81	96	90	85	81	88	83	80		86	82	79		84
5	93	85	80	75	92	84	79	75	83	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	70		77	72	69		75
7	85	76	70	66	83	75	69	65	74	69	65		72	68	65		71
8	81	71	65	61	79	71	65	61	70	65	61		69	64	61		68
9	77	67	62	58	76	67	61	58	66	61	57		65	61	57		64
10	73	64	58	54	72	63	58	54	63	58	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	500442
5°	472440
10°	460156
15°	449628
20°	418076
25°	373739
30°	285462
35°	164818
40°	63977
45°	26638
50°	5868
55°	879
60°	702
65°	415
70°	513
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 26638 cd/sqm

TEST NUMBER: P1276948

CATALOG NUMBER: P3AS20R609835D010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	202.6	10.6
10°-20°	551.7	28.9
20°-30°	691.0	36.2
30°-40°	386.3	20.2
40°-50°	73.4	3.8
50°-60°	3.8	0.2
60°-70°	0.9	0.0
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1445.4	75.7
0°-40°	1831.6	95.9
0°-60°	1908.8	99.9
0°-90°	1910.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1910.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2282	
5°	2146	203
15°	1981	552
25°	1545	691
35°	616	386
45°	86	73
55°	2	4
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1276948

CATALOG NUMBER: P3AS20R609835D010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	2282.2
1°	2272.8
2°	2243.2
3°	2208.0
4°	2175.2
5°	2146.3
6°	2124.4
7°	2105.6
8°	2091.6
9°	2078.3
10°	2066.6
11°	2054.9
12°	2041.6
13°	2025.2
14°	2005.6
15°	1980.6
16°	1950.2
17°	1915.8
18°	1876.7
19°	1832.2
20°	1791.6
21°	1747.8
22°	1702.5
23°	1654.8
24°	1602.5
25°	1544.7
26°	1476.7
27°	1400.9
28°	1315.7
29°	1225.1
30°	1127.4
31°	1029.0
32°	927.4
32.5°	871.9
33°	821.9
34°	718.0
35°	615.7
36°	523.5
37°	425.8
37.5°	381.3
38°	337.5
39°	271.9
40°	223.5
42.5°	135.9
45°	85.9



TEST NUMBER: P1276948

CATALOG NUMBER: P3AS20R609835D010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	47.7
50°	17.2
52.5°	3.9
55°	2.3
57.5°	1.6
60°	1.6
62.5°	0.8
65°	0.8
67.5°	0.8
70°	0.8
72.5°	0.8
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)