

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276963

Luminaire Tested: P3AS20R609835D010 E3DLP1H

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1276963  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-37)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS20R609835D010 E3DLP1H  
Description: 3in Adjustable LED luminaire with, R60 optic, 3500K CCT AND, 98CRI , E3DLP1H TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1159.0 lumens  
Efficiency: N/A  
Efficacy: 42.3 lumens/watt  
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 27.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1276963

CATALOG NUMBER: P3AS20R609835D010 E3DLP1H

### Luminous Intensity Polar Plot



TEST NUMBER: P1276963

CATALOG NUMBER: P3AS20R609835D010 E3DLP1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 107 | 105 | 110 | 108 | 105 | 103 | 104 | 102 | 100 |  | 100 | 98  | 97  |  | 96  |
| 2   | 107 | 101 | 97  | 93  | 104 | 100 | 96  | 92  | 96  | 93  | 90  |  | 93  | 91  | 88  |  | 91  |
| 3   | 101 | 94  | 88  | 84  | 99  | 92  | 87  | 83  | 90  | 86  | 82  |  | 87  | 84  | 81  |  | 85  |
| 4   | 95  | 87  | 81  | 77  | 93  | 86  | 80  | 76  | 84  | 79  | 75  |  | 82  | 78  | 74  |  | 80  |
| 5   | 90  | 81  | 75  | 70  | 88  | 80  | 74  | 70  | 78  | 73  | 69  |  | 77  | 72  | 69  |  | 75  |
| 6   | 85  | 76  | 69  | 65  | 84  | 75  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 71  |
| 7   | 81  | 71  | 65  | 60  | 79  | 70  | 64  | 60  | 69  | 64  | 60  |  | 68  | 63  | 59  |  | 67  |
| 8   | 77  | 67  | 60  | 56  | 75  | 66  | 60  | 56  | 65  | 60  | 56  |  | 64  | 59  | 55  |  | 63  |
| 9   | 73  | 63  | 57  | 52  | 72  | 62  | 56  | 52  | 61  | 56  | 52  |  | 60  | 55  | 52  |  | 60  |
| 10  | 69  | 59  | 53  | 49  | 68  | 59  | 53  | 49  | 58  | 53  | 49  |  | 57  | 52  | 49  |  | 56  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 293726 |
| 5°  | 287144 |
| 10° | 268822 |
| 15° | 241182 |
| 20° | 207405 |
| 25° | 171494 |
| 30° | 135515 |
| 35° | 100626 |
| 40° | 69301  |
| 45° | 43477  |
| 50° | 23914  |
| 55° | 13992  |
| 60° | 12587  |
| 65° | 10740  |
| 70° | 9168   |
| 75° | 9404   |
| 80° | 8082   |
| 85° | 8051   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 43477 cd/sqm

TEST NUMBER: P1276963

CATALOG NUMBER: P3AS20R609835D010 E3DLP1H

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 121.4  | 10.5      |
| 10°-20°   | 295.0  | 25.5      |
| 20°-30°   | 323.6  | 27.9      |
| 30°-40°   | 235.8  | 20.3      |
| 40°-50°   | 111.4  | 9.6       |
| 50°-60°   | 36.5   | 3.1       |
| 60°-70°   | 20.7   | 1.8       |
| 70°-80°   | 11.1   | 1.0       |
| 80°-90°   | 3.5    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 740.1  | 63.9      |
| 0°-40°    | 975.9  | 84.2      |
| 0°-60°    | 1123.8 | 97.0      |
| 0°-90°    | 1159.0 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 1159.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1340 |      |
| 5°  | 1304 | 121  |
| 15° | 1062 | 295  |
| 25° | 709  | 324  |
| 35° | 376  | 236  |
| 45° | 140  | 111  |
| 55° | 37   | 36   |
| 65° | 21   | 21   |
| 75° | 11   | 11   |
| 85° | 3    | 3    |
| 90° | 0    |      |

TEST NUMBER: P1276963

CATALOG NUMBER: P3AS20R609835D010 E3DLP1H

**CANDELA DISTRIBUTION (FULL):**

|       | 0°     |
|-------|--------|
| 0°    | 1339.5 |
| 2.5°  | 1331.5 |
| 5°    | 1304.5 |
| 7.5°  | 1263.0 |
| 10°   | 1207.3 |
| 12.5° | 1140.4 |
| 15°   | 1062.4 |
| 17.5° | 977.9  |
| 20°   | 888.8  |
| 22.5° | 798.0  |
| 25°   | 708.8  |
| 27.5° | 619.6  |
| 30°   | 535.2  |
| 32.5° | 453.9  |
| 35°   | 375.9  |
| 37.5° | 305.8  |
| 40°   | 242.1  |
| 42.5° | 186.4  |
| 45°   | 140.2  |
| 47.5° | 101.9  |
| 50°   | 70.1   |
| 52.5° | 46.2   |
| 55°   | 36.6   |
| 57.5° | 31.9   |
| 60°   | 28.7   |
| 62.5° | 23.9   |
| 65°   | 20.7   |
| 67.5° | 17.5   |
| 70°   | 14.3   |
| 72.5° | 12.7   |
| 75°   | 11.1   |
| 77.5° | 8.0    |
| 80°   | 6.4    |
| 82.5° | 4.8    |
| 85°   | 3.2    |
| 87.5° | 1.6    |
| 90°   | 0.0    |

(END OF REPORT)