

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1276964

Luminaire Tested: P3AS20R609835D010 E3DLP1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1276964
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-37)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R609835D010 E3DLP1LI
Description: 3in Adjustable LED luminaire with, R60 optic, 3500K CCT AND, 98CRI , E3DLP1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1159.0 lumens
Efficiency: N/A
Efficacy: 42.3 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1276964

CATALOG NUMBER: P3AS20R609835D010 E3DLP1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1276964

CATALOG NUMBER: P3AS20R609835D010 E3DLP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	107	101	97	93	104	100	96	92	96	93	90		93	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	77	93	86	80	76	84	79	75		82	78	74		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	76	69	65	84	75	69	65	73	68	64		72	67	64		71
7	81	71	65	60	79	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	60	56		64	59	55		63
9	73	63	57	52	72	62	56	52	61	56	52		60	55	52		60
10	69	59	53	49	68	59	53	49	58	53	49		57	52	49		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	293726
5°	287144
10°	268822
15°	241182
20°	207405
25°	171494
30°	135515
35°	100626
40°	69301
45°	43477
50°	23914
55°	13992
60°	12587
65°	10740
70°	9168
75°	9404
80°	8082
85°	8051

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 43477 cd/sqm

TEST NUMBER: P1276964

CATALOG NUMBER: P3AS20R609835D010 E3DLP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	121.4	10.5
10°-20°	295.0	25.5
20°-30°	323.6	27.9
30°-40°	235.8	20.3
40°-50°	111.4	9.6
50°-60°	36.5	3.1
60°-70°	20.7	1.8
70°-80°	11.1	1.0
80°-90°	3.5	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	740.1	63.9
0°-40°	975.9	84.2
0°-60°	1123.8	97.0
0°-90°	1159.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1159.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1340	
5°	1304	121
15°	1062	295
25°	709	324
35°	376	236
45°	140	111
55°	37	36
65°	21	21
75°	11	11
85°	3	3
90°	0	

TEST NUMBER: P1276964

CATALOG NUMBER: P3AS20R609835D010 E3DLP1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1339.5
2.5°	1331.5
5°	1304.5
7.5°	1263.0
10°	1207.3
12.5°	1140.4
15°	1062.4
17.5°	977.9
20°	888.8
22.5°	798.0
25°	708.8
27.5°	619.6
30°	535.2
32.5°	453.9
35°	375.9
37.5°	305.8
40°	242.1
42.5°	186.4
45°	140.2
47.5°	101.9
50°	70.1
52.5°	46.2
55°	36.6
57.5°	31.9
60°	28.7
62.5°	23.9
65°	20.7
67.5°	17.5
70°	14.3
72.5°	12.7
75°	11.1
77.5°	8.0
80°	6.4
82.5°	4.8
85°	3.2
87.5°	1.6
90°	0.0

(END OF REPORT)