

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1281277

Luminaire Tested: P3AS05R30B2750DE010 E3CB1MW_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1281277
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R30B2750DE010 E3CB1MW_2700K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R30 optic, 2700K CCT AND, 90CRI , E3CB1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 505.0 lumens
Efficiency: N/A
Efficacy: 85.6 lumens/watt
Spacing Criteria (0/90/45): 0.53 / 0.53 / 0.47
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 5.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1281277

CATALOG NUMBER: P3AS05R30B2750DE010 E3CB1MW_2700K

Luminous Intensity Polar Plot





TEST NUMBER: P1281277

CATALOG NUMBER: P3AS05R30B2750DE010 E3CB1MW_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98	97			
2	111	108	105	102	109	106	104	101	103	101	99	100	99	97	98	96	95	94			
3	108	103	100	97	106	102	99	96	100	97	95	97	95	93	95	94	92	91			
4	105	100	96	93	103	99	95	92	97	94	91	95	92	90	93	91	89	88			
5	102	96	92	89	100	95	91	89	94	90	88	92	89	87	91	88	87	85			
6	99	93	89	86	98	92	88	86	91	88	85	90	87	85	89	86	84	83			
7	96	90	86	83	95	89	86	83	88	85	82	87	84	82	86	84	82	81			
8	94	87	83	81	93	87	83	80	86	83	80	85	82	80	84	82	80	79			
9	91	85	81	78	90	84	81	78	84	80	78	83	80	78	82	79	77	77			
10	89	83	79	76	88	82	78	76	82	78	76	81	78	76	80	77	75	75			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	411239
5°	403477
10°	357174
15°	226290
20°	85897
25°	25429
30°	10052
35°	3078
40°	1374
45°	496
50°	409
55°	306
60°	351
65°	415
70°	256
75°	339
80°	505
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 80°

Luminance: 505 cd/sqm

TEST NUMBER: P1281277

CATALOG NUMBER: P3AS05R30B2750DE010 E3CB1MW_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	168.5	33.4
10°-20°	262.6	52.0
20°-30°	61.0	12.1
30°-40°	9.4	1.9
40°-50°	1.6	0.3
50°-60°	0.8	0.2
60°-70°	0.6	0.1
70°-80°	0.4	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	492.1	97.4
0°-40°	501.5	99.3
0°-60°	503.9	99.8
0°-90°	505.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	505.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1875	
5°	1833	168
15°	997	263
25°	105	61
35°	12	9
45°	2	2
55°	1	1
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1281277

CATALOG NUMBER: P3AS05R30B2750DE010 E3CB1MW_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1875.4
1°	1874.2
2°	1869.1
3°	1860.3
4°	1849.2
5°	1833.0
6°	1812.7
7°	1782.6
8°	1741.3
9°	1680.6
10°	1604.1
11°	1505.3
12°	1393.9
13°	1270.1
14°	1134.0
15°	996.8
17.5°	652.1
20°	368.1
22.5°	188.0
25°	105.1
27.5°	64.7
30°	39.7
32.5°	21.4
35°	11.5
37.5°	7.5
40°	4.8
42.5°	2.8
45°	1.6
47.5°	1.2
50°	1.2
52.5°	0.8
55°	0.8
57.5°	0.8
60°	0.8
62.5°	0.8
65°	0.8
67.5°	0.4
70°	0.4
72.5°	0.4
75°	0.4
77.5°	0.4
80°	0.4
82.5°	0.0
85°	0.0
87.5°	0.0



TEST NUMBER: P1281277

CATALOG NUMBER: P3AS05R30B2750DE010 E3CB1MW_2700K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)