

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1282674

Luminaire Tested: P3AS09R15B2750DE010 E3DLP1MW\_3500K

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1282674  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-1)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS09R15B2750DE010 E3DLP1MW\_3500K  
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R15 optic, 3500K CCT AND, 80CRI , E3DLP1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 364.0 lumens  
Efficiency: N/A  
Efficacy: 27.8 lumens/watt  
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.61  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 13.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1282674

CATALOG NUMBER: P3AS09R15B2750DE010 E3DLP1MW\_3500K

### Luminous Intensity Polar Plot



TEST NUMBER: P1282674

CATALOG NUMBER: P3AS09R15B2750DE010 E3DLP1MW\_3500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 108 | 106 | 111 | 108 | 106 | 104 | 104 | 102 | 101 |  | 100 | 99  | 98  |  | 97  |
| 2   | 108 | 103 | 98  | 95  | 105 | 101 | 97  | 94  | 98  | 95  | 92  |  | 95  | 92  | 90  |  | 92  |
| 3   | 102 | 96  | 91  | 87  | 100 | 94  | 90  | 86  | 92  | 88  | 85  |  | 89  | 86  | 83  |  | 87  |
| 4   | 97  | 90  | 84  | 80  | 95  | 88  | 83  | 79  | 86  | 82  | 78  |  | 84  | 81  | 78  |  | 82  |
| 5   | 93  | 84  | 78  | 74  | 91  | 83  | 78  | 74  | 81  | 77  | 73  |  | 80  | 76  | 72  |  | 78  |
| 6   | 88  | 79  | 73  | 69  | 87  | 79  | 73  | 69  | 77  | 72  | 69  |  | 76  | 71  | 68  |  | 74  |
| 7   | 84  | 75  | 69  | 65  | 83  | 74  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 71  |
| 8   | 80  | 71  | 65  | 61  | 79  | 71  | 65  | 61  | 69  | 64  | 61  |  | 68  | 64  | 61  |  | 67  |
| 9   | 77  | 68  | 62  | 58  | 76  | 67  | 62  | 58  | 66  | 61  | 58  |  | 65  | 61  | 57  |  | 64  |
| 10  | 74  | 64  | 59  | 55  | 73  | 64  | 59  | 55  | 63  | 58  | 55  |  | 62  | 58  | 55  |  | 62  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 156961 |
| 5°  | 145080 |
| 10° | 115830 |
| 15° | 87492  |
| 20° | 66622  |
| 25° | 50761  |
| 30° | 36360  |
| 35° | 23744  |
| 40° | 14542  |
| 45° | 8807   |
| 50° | 5833   |
| 55° | 4511   |
| 60° | 3903   |
| 65° | 3373   |
| 70° | 3013   |
| 75° | 2965   |
| 80° | 2273   |
| 85° | 1510   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
Vertical Angle: 45°  
Luminance: 8807 cd/sqm

TEST NUMBER: P1282674

CATALOG NUMBER: P3AS09R15B2750DE010 E3DLP1MW\_3500K

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 58.4   | 16.0      |
| 10°-20°   | 107.7  | 29.6      |
| 20°-30°   | 95.9   | 26.3      |
| 30°-40°   | 56.7   | 15.6      |
| 40°-50°   | 23.3   | 6.4       |
| 50°-60°   | 10.9   | 3.0       |
| 60°-70°   | 6.7    | 1.8       |
| 70°-80°   | 3.5    | 1.0       |
| 80°-90°   | 0.9    | 0.2       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 262.0  | 72.0      |
| 0°-40°    | 318.8  | 87.6      |
| 0°-60°    | 353.0  | 97.0      |
| 0°-90°    | 364.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 364.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 716 |      |
| 5°  | 659 | 58   |
| 15° | 385 | 108  |
| 25° | 210 | 96   |
| 35° | 89  | 57   |
| 45° | 28  | 23   |
| 55° | 12  | 11   |
| 65° | 6   | 7    |
| 75° | 4   | 3    |
| 85° | 1   | 1    |
| 90° | 0   |      |

TEST NUMBER: P1282674

CATALOG NUMBER: P3AS09R15B2750DE010 E3DLP1MW\_3500K

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 715.8 |
| 1°    | 714.0 |
| 2°    | 708.7 |
| 3°    | 698.1 |
| 4°    | 680.4 |
| 5°    | 659.1 |
| 6°    | 636.0 |
| 7°    | 608.8 |
| 8°    | 580.5 |
| 9°    | 551.5 |
| 10°   | 520.2 |
| 12.5° | 448.6 |
| 15°   | 385.4 |
| 17.5° | 331.0 |
| 20°   | 285.5 |
| 22.5° | 245.3 |
| 25°   | 209.8 |
| 27.5° | 175.6 |
| 30°   | 143.6 |
| 32.5° | 114.7 |
| 35°   | 88.7  |
| 37.5° | 68.0  |
| 40°   | 50.8  |
| 42.5° | 37.8  |
| 45°   | 28.4  |
| 47.5° | 21.9  |
| 50°   | 17.1  |
| 52.5° | 14.2  |
| 55°   | 11.8  |
| 57.5° | 10.0  |
| 60°   | 8.9   |
| 62.5° | 7.7   |
| 65°   | 6.5   |
| 67.5° | 5.9   |
| 70°   | 4.7   |
| 72.5° | 4.1   |
| 75°   | 3.5   |
| 77.5° | 2.4   |
| 80°   | 1.8   |
| 82.5° | 1.2   |
| 85°   | 0.6   |
| 87.5° | 0.6   |
| 90°   | 0.0   |

(END OF REPORT)