

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1282923

Luminaire Tested: P3AS09R25B2750DE010 E3DLD1H_3000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1282923
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R25B2750DE010 E3DLD1H_3000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R25 optic, 3000K CCT AND, 90CRI , E3DLD1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 463.0 lumens
Efficiency: N/A
Efficacy: 35.3 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 13.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1282923

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1H_3000K

Luminous Intensity Polar Plot





TEST NUMBER: P1282923

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1H_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	110035
5°	107418
10°	99531
15°	88650
20°	76190
25°	64746
30°	53299
35°	41546
40°	29885
45°	18948
50°	11224
55°	7723
60°	7105
65°	6590
70°	5898
75°	5338
80°	5051
85°	4277

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 18948 cd/sqm

TEST NUMBER: P1282923

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1H_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	45.3	9.8
10°-20°	108.4	23.4
20°-30°	122.5	26.5
30°-40°	96.9	20.9
40°-50°	48.9	10.6
50°-60°	19.6	4.2
60°-70°	12.6	2.7
70°-80°	6.9	1.5
80°-90°	2.0	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	276.1	59.6
0°-40°	373.0	80.6
0°-60°	441.6	95.4
0°-90°	463.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	463.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	502	
5°	488	45
15°	390	108
25°	268	122
35°	155	97
45°	61	49
55°	20	20
65°	13	13
75°	6	7
85°	2	2
90°	0	

TEST NUMBER: P1282923

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1H_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	501.8
1°	501.8
2°	500.1
3°	497.2
4°	493.2
5°	488.0
6°	481.6
7°	474.1
8°	466.1
9°	456.8
10°	447.0
11°	436.1
12°	425.7
13°	413.6
14°	402.0
15°	390.5
17.5°	358.2
20°	326.5
22.5°	296.5
25°	267.6
27.5°	239.4
30°	210.5
32.5°	183.4
35°	155.2
37.5°	129.2
40°	104.4
42.5°	81.3
45°	61.1
47.5°	45.6
50°	32.9
52.5°	24.8
55°	20.2
57.5°	18.5
60°	16.2
62.5°	14.4
65°	12.7
67.5°	11.0
70°	9.2
72.5°	8.1
75°	6.3
77.5°	5.2
80°	4.0
82.5°	2.9
85°	1.7
87.5°	0.6



TEST NUMBER: P1282923

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1H_3000K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)