

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1282941

Luminaire Tested: P3AS09R25B2750DE010 E3DLD1WH_5000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1282941
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R25B2750DE010 E3DLD1WH_5000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R25 optic, 5000K CCT AND, 80CRI , E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 503.0 lumens
Efficiency: N/A
Efficacy: 38.4 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 13.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1282941

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1WH_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1282941

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1WH_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	119552
5°	116685
10°	108125
15°	96300
20°	82771
25°	70359
30°	57908
35°	45133
40°	32461
45°	20591
50°	12179
55°	8372
60°	7675
65°	7160
70°	6411
75°	5846
80°	5556
85°	4780

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 20591 cd/sqm

TEST NUMBER: P1282941

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1WH_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	49.2	9.8
10°-20°	117.8	23.4
20°-30°	133.1	26.5
30°-40°	105.3	20.9
40°-50°	53.2	10.6
50°-60°	21.3	4.2
60°-70°	13.6	2.7
70°-80°	7.5	1.5
80°-90°	2.1	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	300.0	59.6
0°-40°	405.3	80.6
0°-60°	479.7	95.4
0°-90°	503.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	503.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	545	
5°	530	49
15°	424	118
25°	291	133
35°	169	105
45°	66	53
55°	22	21
65°	14	14
75°	7	8
85°	2	2
90°	0	

TEST NUMBER: P1282941

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1WH_5000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	545.2
1°	545.2
2°	543.3
3°	540.2
4°	535.8
5°	530.1
6°	523.2
7°	515.1
8°	506.3
9°	496.3
10°	485.6
11°	473.7
12°	462.5
13°	449.3
14°	436.8
15°	424.2
17.5°	389.1
20°	354.7
22.5°	322.1
25°	290.8
27.5°	260.1
30°	228.7
32.5°	199.3
35°	168.6
37.5°	140.4
40°	113.4
42.5°	88.4
45°	66.4
47.5°	49.5
50°	35.7
52.5°	26.9
55°	21.9
57.5°	20.1
60°	17.5
62.5°	15.7
65°	13.8
67.5°	11.9
70°	10.0
72.5°	8.8
75°	6.9
77.5°	5.6
80°	4.4
82.5°	3.1
85°	1.9
87.5°	0.6



TEST NUMBER: P1282941

CATALOG NUMBER: P3AS09R25B2750DE010 E3DLD1WH_5000K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)