

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1283046

Luminaire Tested: P3AS09R30B2750DE010 E3D1WMH_5000K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1283046
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R30B2750DE010 E3D1WMH_5000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R30 optic, 5000K CCT AND, 80CRI , E3D1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 791.0 lumens
Efficiency: N/A
Efficacy: 60.4 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.47
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 13.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1283046

CATALOG NUMBER: P3AS09R30B2750DE010 E3D1WMH_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1283046

CATALOG NUMBER: P3AS09R30B2750DE010 E3D1WMH_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98
2	111	108	105	102	109	106	103	101	103	101	99	100	98	97	97	96	95
3	108	103	100	97	106	102	99	96	99	97	95	97	95	93	95	93	92
4	105	99	95	92	103	98	95	92	96	93	91	94	92	90	93	91	89
5	101	96	92	89	100	95	91	88	93	90	87	92	89	87	90	88	86
6	99	92	88	85	97	92	88	85	90	87	85	89	86	84	88	85	83
7	96	89	85	82	95	89	85	82	88	84	82	87	84	81	86	83	81
8	93	87	83	80	92	86	82	80	85	82	79	84	81	79	84	81	79
9	91	84	80	77	90	84	80	77	83	79	77	82	79	77	82	79	77
10	88	82	78	75	88	81	78	75	81	77	75	80	77	75	80	77	75

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	629336
5°	621130
10°	542319
15°	344701
20°	136559
25°	45607
30°	21218
35°	9610
40°	3693
45°	1799
50°	512
55°	229
60°	132
65°	156
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 1799 cd/sqm

TEST NUMBER: P1283046

CATALOG NUMBER: P3AS09R30B2750DE010 E3D1WMH_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	258.0	32.6
10°-20°	400.1	50.6
20°-30°	103.2	13.0
30°-40°	24.2	3.1
40°-50°	4.7	0.6
50°-60°	0.5	0.1
60°-70°	0.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	761.2	96.2
0°-40°	785.5	99.3
0°-60°	790.7	100.0
0°-90°	791.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	791.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2870	
5°	2822	258
15°	1518	400
25°	188	103
35°	36	24
45°	6	5
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1283046

CATALOG NUMBER: P3AS09R30B2750DE010 E3D1WMH_5000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	2870.0
1°	2867.9
2°	2861.1
3°	2853.5
4°	2842.1
5°	2821.8
6°	2789.0
7°	2734.3
8°	2659.7
9°	2562.4
10°	2435.6
11°	2284.8
12°	2120.2
13°	1930.8
14°	1732.4
15°	1518.4
16°	1308.7
17°	1106.6
18°	912.9
19°	735.1
20°	585.2
21°	460.6
22°	362.3
23°	286.8
24°	229.7
25°	188.5
26°	157.2
27°	133.6
28°	115.5
29°	98.9
30°	83.8
32.5°	52.8
35°	35.9
37.5°	22.4
40°	12.9
42.5°	8.6
45°	5.8
47.5°	3.4
50°	1.5
52.5°	0.6
55°	0.6
57.5°	0.3
60°	0.3
62.5°	0.3
65°	0.3



TEST NUMBER: P1283046

CATALOG NUMBER: P3AS09R30B2750DE010 E3D1WMH_5000K

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)