

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1283097

Luminaire Tested: P3AS09R30B2750DE010 E3DLD1WH_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1283097
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R30B2750DE010 E3DLD1WH_2700K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R30 optic, 2700K CCT AND, 90CRI , E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 477.0 lumens
Efficiency: N/A
Efficacy: 36.4 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 13.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1283097

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_2700K

Luminous Intensity Polar Plot



TEST NUMBER: P1283097

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		84
4	94	85	79	74	92	84	79	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	112688
5°	110169
10°	102447
15°	91147
20°	78407
25°	66415
30°	55122
35°	43259
40°	31001
45°	20343
50°	11565
55°	7608
60°	7192
65°	6693
70°	6027
75°	5422
80°	5177
85°	4529

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 20343 cd/sqm

TEST NUMBER: P1283097

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	46.5	9.7
10°-20°	111.6	23.4
20°-30°	125.8	26.4
30°-40°	100.5	21.1
40°-50°	51.6	10.8
50°-60°	19.4	4.1
60°-70°	12.7	2.7
70°-80°	6.9	1.4
80°-90°	2.0	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	283.9	59.5
0°-40°	384.3	80.6
0°-60°	455.4	95.5
0°-90°	477.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	477.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	514	
5°	500	46
15°	402	112
25°	274	126
35°	162	100
45°	66	52
55°	20	19
65°	13	13
75°	6	7
85°	2	2
90°	0	

TEST NUMBER: P1283097

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	513.9
1°	513.9
2°	512.2
3°	509.2
4°	505.1
5°	500.5
6°	494.6
7°	487.0
8°	478.8
9°	469.4
10°	460.1
11°	449.5
12°	438.4
13°	426.7
14°	414.4
15°	401.5
17.5°	368.8
20°	336.0
22.5°	304.4
25°	274.5
27.5°	245.3
30°	217.7
32.5°	189.6
35°	161.6
37.5°	134.0
40°	108.3
42.5°	85.5
45°	65.6
47.5°	48.6
50°	33.9
52.5°	24.0
55°	19.9
57.5°	18.1
60°	16.4
62.5°	14.6
65°	12.9
67.5°	11.1
70°	9.4
72.5°	7.6
75°	6.4
77.5°	5.3
80°	4.1
82.5°	2.9
85°	1.8
87.5°	0.6



TEST NUMBER: P1283097

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_2700K

CANDELA DISTRIBUTION (continued):



(END OF REPORT)