

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1283101

Luminaire Tested: P3AS09R30B2750DE010 E3DLD1WH_5000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1283101
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R30B2750DE010 E3DLD1WH_5000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R30 optic, 5000K CCT AND, 80CRI , E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 510.0 lumens
Efficiency: N/A
Efficacy: 38.9 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 13.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1283101

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1283101

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		84
4	94	85	79	74	92	84	79	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	120495
5°	117785
10°	109528
15°	97458
20°	83821
25°	71012
30°	58946
35°	46230
40°	33148
45°	21739
50°	12383
55°	8143
60°	7675
65°	7160
70°	6411
75°	5846
80°	5556
85°	4780

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 21739 cd/sqm

TEST NUMBER: P1283101

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	49.7	9.7
10°-20°	119.3	23.4
20°-30°	134.5	26.4
30°-40°	107.4	21.1
40°-50°	55.2	10.8
50°-60°	20.8	4.1
60°-70°	13.6	2.7
70°-80°	7.3	1.4
80°-90°	2.1	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	303.5	59.5
0°-40°	410.9	80.6
0°-60°	486.9	95.5
0°-90°	510.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	510.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	550	
5°	535	50
15°	429	119
25°	294	134
35°	173	107
45°	70	55
55°	21	21
65°	14	14
75°	7	7
85°	2	2
90°	0	

TEST NUMBER: P1283101

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_5000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	549.5
1°	549.5
2°	547.6
3°	544.5
4°	540.1
5°	535.1
6°	528.8
7°	520.7
8°	511.9
9°	501.9
10°	491.9
11°	480.6
12°	468.7
13°	456.2
14°	443.1
15°	429.3
17.5°	394.3
20°	359.2
22.5°	325.4
25°	293.5
27.5°	262.2
30°	232.8
32.5°	202.8
35°	172.7
37.5°	143.3
40°	115.8
42.5°	91.4
45°	70.1
47.5°	51.9
50°	36.3
52.5°	25.7
55°	21.3
57.5°	19.4
60°	17.5
62.5°	15.6
65°	13.8
67.5°	11.9
70°	10.0
72.5°	8.1
75°	6.9
77.5°	5.6
80°	4.4
82.5°	3.1
85°	1.9
87.5°	0.6



TEST NUMBER: P1283101

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLD1WH_5000K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)