

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1283113

Luminaire Tested: P3AS09R30B2750DE010 E3DLP1H\_3000K

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1283113  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-13)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS09R30B2750DE010 E3DLP1H\_3000K  
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R30 optic, 3000K CCT AND, 90CRI , E3DLP1H TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 372.0 lumens  
Efficiency: N/A  
Efficacy: 28.4 lumens/watt  
Spacing Criteria (0/90/45): 0.66 / 0.66 / 0.7  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 13.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1283113

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLP1H\_3000K

### Luminous Intensity Polar Plot



TEST NUMBER: P1283113

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLP1H\_3000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| RF  | 20  |     |     |     | 20  |     |     |     |     | 20  |     |     |     |     | 20  |     |     |     |    | 20 |
| RC  | 80  |     |     |     | 70  |     |     |     |     | 50  |     |     |     |     | 30  |     |     |     |    | 0  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30 | 10 |
| RCR |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |    |    |
| 1   | 113 | 110 | 108 | 105 | 111 | 108 | 106 | 104 | 104 | 102 | 100 | 100 | 99  | 97  | 97  | 96  | 95  | 93  |    |    |
| 2   | 107 | 102 | 98  | 95  | 105 | 101 | 97  | 94  | 97  | 94  | 92  | 94  | 92  | 90  | 92  | 90  | 88  | 86  |    |    |
| 3   | 102 | 95  | 90  | 86  | 100 | 94  | 89  | 85  | 91  | 87  | 84  | 89  | 86  | 83  | 87  | 84  | 82  | 80  |    |    |
| 4   | 97  | 89  | 84  | 79  | 95  | 88  | 83  | 79  | 86  | 81  | 78  | 84  | 80  | 77  | 82  | 79  | 76  | 74  |    |    |
| 5   | 92  | 84  | 78  | 73  | 90  | 83  | 77  | 73  | 81  | 76  | 72  | 79  | 75  | 72  | 78  | 74  | 71  | 70  |    |    |
| 6   | 88  | 79  | 73  | 68  | 86  | 78  | 72  | 68  | 76  | 71  | 68  | 75  | 71  | 67  | 74  | 70  | 67  | 65  |    |    |
| 7   | 83  | 74  | 68  | 64  | 82  | 74  | 68  | 64  | 72  | 67  | 63  | 71  | 67  | 63  | 70  | 66  | 63  | 61  |    |    |
| 8   | 80  | 70  | 64  | 60  | 78  | 70  | 64  | 60  | 69  | 63  | 60  | 67  | 63  | 60  | 67  | 62  | 59  | 58  |    |    |
| 9   | 76  | 67  | 61  | 57  | 75  | 66  | 60  | 57  | 65  | 60  | 56  | 64  | 60  | 56  | 63  | 59  | 56  | 55  |    |    |
| 10  | 73  | 63  | 58  | 54  | 72  | 63  | 57  | 54  | 62  | 57  | 53  | 61  | 57  | 53  | 60  | 56  | 53  | 52  |    |    |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 127117 |
| 5°  | 123156 |
| 10° | 110975 |
| 15° | 91805  |
| 20° | 71080  |
| 25° | 53301  |
| 30° | 38715  |
| 35° | 25779  |
| 40° | 15858  |
| 45° | 9303   |
| 50° | 5697   |
| 55° | 4626   |
| 60° | 4035   |
| 65° | 3269   |
| 70° | 2949   |
| 75° | 2965   |
| 80° | 2147   |
| 85° | 3019   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
Vertical Angle: 45°  
Luminance: 9303 cd/sqm

TEST NUMBER: P1283113

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLP1H\_3000K

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 51.5   | 13.8      |
| 10°-20°   | 111.4  | 29.9      |
| 20°-30°   | 101.3  | 27.2      |
| 30°-40°   | 61.2   | 16.5      |
| 40°-50°   | 24.6   | 6.6       |
| 50°-60°   | 10.9   | 2.9       |
| 60°-70°   | 6.5    | 1.8       |
| 70°-80°   | 3.6    | 1.0       |
| 80°-90°   | 1.0    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 264.2  | 71.0      |
| 0°-40°    | 325.4  | 87.5      |
| 0°-60°    | 360.9  | 97.0      |
| 0°-90°    | 372.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 372.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 580 |      |
| 5°  | 560 | 51   |
| 15° | 404 | 111  |
| 25° | 220 | 101  |
| 35° | 96  | 61   |
| 45° | 30  | 25   |
| 55° | 12  | 11   |
| 65° | 6   | 7    |
| 75° | 4   | 4    |
| 85° | 1   | 1    |
| 90° | 0   |      |

TEST NUMBER: P1283113

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLP1H\_3000K

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 579.7 |
| 1°    | 579.1 |
| 2°    | 576.8 |
| 3°    | 572.8 |
| 4°    | 567.0 |
| 5°    | 559.5 |
| 6°    | 550.3 |
| 7°    | 540.5 |
| 8°    | 527.8 |
| 9°    | 513.4 |
| 10°   | 498.4 |
| 11°   | 481.1 |
| 12°   | 462.6 |
| 13°   | 444.2 |
| 14°   | 424.0 |
| 15°   | 404.4 |
| 17.5° | 353.0 |
| 20°   | 304.6 |
| 22.5° | 259.6 |
| 25°   | 220.3 |
| 27.5° | 184.6 |
| 30°   | 152.9 |
| 32.5° | 123.4 |
| 35°   | 96.3  |
| 37.5° | 73.8  |
| 40°   | 55.4  |
| 42.5° | 40.4  |
| 45°   | 30.0  |
| 47.5° | 22.5  |
| 50°   | 16.7  |
| 52.5° | 13.3  |
| 55°   | 12.1  |
| 57.5° | 10.4  |
| 60°   | 9.2   |
| 62.5° | 7.5   |
| 65°   | 6.3   |
| 67.5° | 5.8   |
| 70°   | 4.6   |
| 72.5° | 4.0   |
| 75°   | 3.5   |
| 77.5° | 2.9   |
| 80°   | 1.7   |
| 82.5° | 1.2   |
| 85°   | 1.2   |
| 87.5° | 0.6   |



TEST NUMBER: P1283113

CATALOG NUMBER: P3AS09R30B2750DE010 E3DLP1H\_3000K

CANDELA DISTRIBUTION (continued):



(END OF REPORT)